



MAGNETIC STIRRER BER-3911

MAGNETIC STIRRER BER-3911

MAGNETIC STIRRER



1. Heating power and stirring speed is stepless adjustable.
2. With an adjustable thermometer rack, stainless steel rods and the stir bar.
3. SH-(C) series: Ceramic Plate

SPECIFICATIONS

Model	BER-3911
Function	
--Max. Volume (ml)	5000
Speed (r.p.m)	100-2000
Working Time	Continuous
Minimum Revolution (r.p.m)	100
Max.Temp. (°C)	-
Structure	
Exterior	Cast aluminium, Surface spraying / Ceramic Coated
Plate Size(mm)	170x170
Driving Mode	Motor
Motor Power (W)	20
Heating Power(kW)	-
Stir Bar	PTFE
Controller	
Continuous Operation	Yes
Setting Mode	Scale
Speed Display Mode	Scale
Timer	No
Operation Function	No
Temp. Sensor	No
Specification	
Exterior Size (W*L*H)(mm)	265x185x190
Packing Size (W*L*H)(mm)	280x210x220
Plate Size (mm)	170x170
Plate Load	10KG
Power Supply (50/60Hz)	110V or 220V
Current Rating	110V or 220V
NW/GW (kg)	2.2/3.4
Alt Name	Magnetic Stirrer



APPLICATIONS

Magnetic mixing equipment with heating.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com