



MAGNETIC STIRRER BER-4002

MAGNETIC STIRRER BER-4002

CERAMIC MAGNETIC STIRRER



SPECIFICATIONS

Model	BER-4002
Mode	Stirring
Function	
Max. Volume (ML)	5000
Speed (r.p.m)	200-2000
Working Time	Continuous
Minimum Revolution (R.P.M.)	200
Max. Temp (°C)	-
Exterior	Iron plate welding, surface spraying
Heating Plate	Ceramic coated
Driving Mode	Motor
Motor Power (W)	20
Heating Power(kW)	-
Stir Bar	PTFE
Controller	
Continuous Operation	yes
Setting Mode	Scale
Speed Display Mode	Scale
Timer	no
Operation Function	no
Sensor	no
Specification	
Exterior Size (W*L*H)(mm)	320x190x125
Packing Size (W*L*H)(mm)	390x240x230
Plate Size (mm)	190x190
Plate Load	10KG
Power Supply(50/60Hz) Current Rating	110V or 220V
NW/GW (kg)	5/6
Alt Name	Ceramic Magnetic Stirrer



APPLICATIONS

Magnetic stirring ceramic equipment with heating.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com