



MAGNETIC STIRRER BER-4005

MAGNETIC STIRRER BER-4005

CERAMIC MAGNETIC STIRRER



1. Stretched shell and cover prevent leaking.
2. Heating and stirring can proceed simultaneously, Fully enclosed heating plate, no flame, fast heating, strong durability.

New digital model Ceramic Magnetic Stirrer with the following function:

Setting temperature and stirrer speed precisely and no button of stirrer speed.

With a speed switch to start or stop the stirring at any time.

Timing function (0-9999 min), time adjustable under artificial requirement. Audible and visual alarm equipped.

Double sensor: outer PT100 sensor to control liquid temperature precisely, inner K model sensor to control hot plate temperature.

One key to shift inside and outside sensor easily and precisely.

Large display can indicate temperature, rotational speed and timing at the same

SPECIFICATIONS

Model	BER-4005
Mode	Digital + Heating + Stirring
Function	
Max. Volume (ML)	5000
Speed (r.p.m)	200-2000
Working Time	Continuous
Minimum Revolution (R.P.M.)	200
Max. Temp (°C)	350
Exterior	Iron plate welding, surface spraying
Heating Plate	Ceramic coated
Driving Mode	Motor
Motor Power (W)	20
Heating Power(kW)	0.6
Stir Bar	PTFE
Controller	
Continuous Operation	yes
Setting Mode	Digital
Speed Display Mode	Digital
Timer	yes
Operation Function	yes
Sensor	PT100
Specification	
Exterior Size (W*L*H)(mm)	320x190x125
Packing Size (W*L*H)(mm)	390x240x230
Plate Size (mm)	190x190
Plate Load	10KG
Power Supply(50/60Hz) Current Rating	110V or 220V
NW/GW (kg)	5/6
Alt Name	Ceramic Magnetic Stirrer



FEATURES

1. Stretched shell and cover prevent leaking.
 2. Heating and stirring can proceed simultaneously, Fully enclosed heating plate, no flame, fast heating, strong durability.
- New digital model Ceramic Magnetic Stirrer with the following function:
Setting temperature and stirrer speed precisely and no button of stirrer speed.
With a speed switch to start or stop the stirring at any time.
Timing function (0-9999 min), time adjustable under artificial requirement. Audible and visual alarm equipped.
Double sensor: outer PT100 sensor to control liquid temperature precisely, inner K model sensor to control hot plate temperature.
One key to shift inside and outside sensor easily and precisely.
Large display can indicate temperature, rotational speed and timing at the same time.

APPLICATIONS

Magnetic stirring ceramic equipment with heating.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com