



## DRYING OVEN BER-504

# DRYING OVEN BER-504

HOT AIR STERILIZING DRYING OVEN



1. Horizontal air circularly by double Air ducts, high efficiency and high uniformity.
2. PID controller, with over-temperature protection function.
3. With fan switch,LED digital display,high temperature blast motor.
5. New anti-hot handle.

## SPECIFICATIONS

Model	BER-504
Cycle Mode	Forced convection
Function	
--Temp. Range	RT+10-300°C
--Temp. Resolution Ratio	0.1°C
--Temp. Motion	±1°C
--Temp. Uniformity	±2.5%
Structure	
--Inner Chamber	Mirror Stainless Steel
--Quter Shell	Cold rolling steel electrostatic spraying exterior
--Insulation Layer	High quality rock wool board(with CE)
--Heater	Stainless steel heater
--Power Rating	2.0kW
--Exhaust Hole	Φ35mm top(with function of test hole)
Controller	
--Temp. Control Mode	Two temperature section PID intelligent
--Temp. Setting Mode	Touch button setting
--Temp. Display Mode	LED Digital display
--Timer	0-9999min(with timing wait function)
--Operation Function	Fixed temperature operation, timing function, auto stop.
--Additional Function	Sensor deviation correction, temperature overshoot self-tuning, internal parameter locking, power-off parameter memory
--Sensor	PT100
--Safety Device	Over temperature sound-light alarm;
Specification	
--Inner Chamber size(W*L*H)(mm)	450*420*450
--Exterior Size (W*L*H)(mm)	590*610*830
--Packing Size (W*L*H)(mm)	680*685*1000
--Volume	85L
--Max. Shelf Number	8

--Load Per rack	15kg
--Shelf Space	40mm
--Power Rating (50/60HZ)	AC220V/9.0A
--NW/GW (kg)	50/56
Accessory	
--Shelf	2
--Shelf Frame	4
Optional accessories	Spare shelf
Alt Name	Hot Air Sterilizing Drying Oven



## APPLICATIONS

Easy to operate efficient dry heat sterilizer.



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)