



WATER BATH BER-5404

WATER BATH BER-5404

THERMOSTATIC WATER BATHS



1. SHHW21.420All model cover for the two holes water bath, can be used as a digital two holes water bath.
2. SHHW21.600All model cover for the six holes water bath, can be used as a digital six holes water bath.

SPECIFICATIONS

Model	BER-5404
Function	
--Temp Range	RT+5~100°C
--Temp Resolution Ratio	0.1°C
--Temp Motion	±0.5°C
--Temp Uniformity	±1.0°C
Structure	
--Inner Chamber	High quality hairline stainless steel plate
--Outer Shell	Cold rolling steel electrostatic spraying exterior
--Cover	High quality hairline stainless steel plate
--Cover Circle	With
--Test Tube Rack	Without
Controller	
--Heater	Stainless steel heating tube
--Power Rating	2kW
--Temp Control Mode	PID
--Temp Setting Mode	Touch button setting
--Temp Display Mode	Measuring temperature: display on the three digital tubes upper row; setting temperature: display on the lower row
--Timer	0~999min
--Operation Function	Fixed temperature operation, timing function, auto stop.
--Program Function	No
--Additional Function	Deviation correction, Menu key lock, Power-off compensation, Power failure memory
--Sensor	NTC
Safety Device	Over temperature alarm
Specification	
--Sink Size (W*L*H)(mm)	600*300*200
--Exterior Size (W*L*H)(mm)	750*350*360
--Packing Size (W*L*H)(mm)	900*440*440
--Volume	36L
--Supply (50/60Hz) Current Rating	AC220V/9.1A
--NW/Gw (kg)	18/20
Optional Accessories	Different sizes can be customized, can add power off protection function when water shortage.
Alt Name	Thermostatic Water Baths



APPLICATIONS

Used for precision constant temperature and humidity.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com