



VERTICAL LAMINAR AIRFLOW BER1BK4

VERTICAL LAMINAR AIRFLOW BER1BK4

MINI LAMINAR FLOW CABINET



1. HEPA filter with efficiency: 99.995% at 0.3um.
2. Microprocessor control system, LED Display.
3. Front window is 5mm toughened glass, anti-oxidation.
4. Air speed adjustable.
5. Desktop type, with a handle, saving space and easy to move.
6. Pre-filter is polyester fiber, washable and anti-ultraviolet radiation.
7. Automatic cutting off UV lamp function by opening glass.
8. They have color screen LCD controller (with sterilization timing, built-in socket controllable switch , front window status display, can set three position interlock , cumulative work timing, remote control)

SPECIFICATIONS

Model	BER1BK4
Applicable Scope	Protect experiment samples
Airflow Direction	Vertical
Function	
--Cleanliness	Class 100
--High Efficiency Filter	0.3um partial ≥99.999%
--Colony count	≤0.5/vessel (petri dish is Φ90mm)
--Wind Speed	>0.5 (m/s)
--Wind Speed Range	0.2-0.6 (m/s)
--Noise Level	≤62db
--Vibration Semi-peak Value	≤3um
--Work Surface Bearing	10kg
Composition	
--Inner Chamber	SUS304 Stainless steel plate
--Outer Shell	Cold rolling steel electrostatic spraying exterior
--Operation Door	Tempered Glass
--Operation Door Biggest Opening	310mm
--Pre-Filter	Polyurethane
--LED Lamp	8W*1
--UV Lamp	8W*1
--Top Fan	90W one piece
Controller	
--Display	LED (Model II: LCD color screen)
--Wind Speed Control	Intelligent multi-level adjustable
--Additional Function	One key to open and close lighting sterilization
Specification	
--Inner Size (W*L*H) mm	480*340*370
--Exterior Size (W*L*H) mm	550*460*700
--Packing Size (W*L*H) mm	680*590*850
--Max Power	110W
--Current Rating (50/60Hz)	AC220V/0.5A

--NW/GW kg	36/41
Optional Accessories	wind speed sensor
Alt Name	Mini Laminar Flow Cabinet



APPLICATIONS

Table type clean equipment.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com