



MAGNETIC STIRRER BER1BN6

MAGNETIC STIRRER BER1BN6

MAGNETIC STIRRER



1. Heating power and stirring speed is stepless adjustable.
2. With an adjustable thermometer rack, stainless steel rods and the stir bar.
3. SH-(C) series: Ceramic Plate

SPECIFICATIONS

Model	BER1BN6
Function	
Max. Volume (ml)	5000
Speed (r.p.m)	100-2000
Working Time	Continuous
Minimum Revolution (r.p.m)	100
Max.Temp. (°C)	380
Structure	
Exterior	Cast aluminium, Surface spraying / Ceramic Coated
Plate Size(mm)	170x170
Driving Mode	Motor
Motor Power (W)	20
Heating Power(kW)	0.5
Stir Bar	PTFE
Controller	
Continuous Operation	Yes
Setting Mode	Scale
Speed Display Mode	Scale
Timer	No
Operation Function	No
Temp. Sensor	No
Specification	
Exterior Size (W*L*H)(mm)	265x185x190
Packing Size (W*L*H)(mm)	280x210x220
Plate Size (mm)	170x170
Plate Load	10KG
Power Supply (50/60Hz)	110V or 220V
Current Rating	110V or 220V
NW/GW (kg)	2.2/3.4
Alt Name	Magnetic Stirrer



APPLICATIONS

Magnetic mixing equipment with heating.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com