



PORTABLE STERILIZER BER1CM3

PORTABLE STERILIZER BER1CM3

VERTICAL PRESSURE STEAM STERILIZER



1. Fully stainless steel structure.
2. Hand wheel type of quick-open door structure.
3. Door safety lock system.
4. Digital display of working status, touch of key.
5. Self-inflating type seal.
6. Over temperature & over pressure auto-protection.
7. Safe protection of water lacking.
6. Automatically shut off with beep reminding after sterilization.
7. Auto discharge the cool air, and steam discharging automatically after sterilization.
8. Used for sterilization of medical instruments, medical cotton products.
9. Fully stainless steel SUS304 / AISI 304 - 3mm.

SPECIFICATIONS

Model	BER1CM3
Capacity	75L(Φ400*600)mm
Working pressure	0.22Mpa
Working temperature	134℃
Max.working pressure	0.23Mpa
Heat average	≤ ± 1℃
Timer	0-99min or 0-99hour59 min
Temp.range	105℃~134℃
Power	4.5KW/AC220V.50Hz
Exterior size	560*560*1120mm
Packing size	650*630*1280mm
G.W/N.W	100kg/80kg
Alt Name	Vertical Pressure Steam Sterilizer



FEATURES

1. Fully stainless steel structure.
2. Hand wheel type of quick-open door structure.
3. Door safety lock system.
4. Digital display of working status, touch of key.
5. Self-inflating type seal.
6. Over temperature & over pressure auto-protection.
7. Safe protection of water lacking.
6. Automatically shut off with beep reminding after sterilization.
7. Auto discharge the cool air, and steam discharging automatically after sterilization.
8. Used for sterilization of medical instruments, medical cotton products.

9. Fully stainless steel SUS304 / AISI 304 - 3mm.
10. Possible to install drying system according request.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com