



HOT AIR OVEN BER1DD6

HOT AIR OVEN BER1DD6

HOT AIR STERILIZING DRYING OVEN



1. Horizontal air circularly by double Air ducts, high efficiency and high uniformity.
2. PID controller, with over-temperature protection function.
3. New anti-hot handle.
4. LCD temperature controller.
5. 4 grades speed fan, adjustable for different requirements.
6. Over-temperature protection system.
7. High precision digital independent temperature limiter.

SPECIFICATIONS

Model	BER1DD6
Cycle Mode	Forced convection
Function	
--Temp. Range	RT+10-300°C
--Temp. Resolution Ratio	0.1°C
--Temp. Motion	±1°C
--Temp. Uniformity	±2.5%
Structure	
--Inner Chamber	SUS304
--Outer Shell	SUS304
--Insulation Layer	High quality rockwool board (with CE)
--Heater	Stainless steel heater
--Power Rating	3.0kW
--Exhaust Hole	Rear exhaust
Controller	
--Temp. Control Mode	Two temperature section PID intelligent
--Temp. Setting Mode	Touch button setting
--Temp. Display Mode	LCD Digital display
--Timer	0-9999min (with timing wait function)
--Operation Function	Fixed temperature operation, fixed timing operation, auto stop.
--Additional Function	Sensor deviation correction, temperature overshoot self-tuning, internal parameter locking, power-off parameter memory.
--Sensor	PT100
Safety Device	Digital Independent Temp. limiter, Over temperature sound-light alarm.
Specification	
--Inner Chamber Size(W*L*H)(mm)	600*500*750
--Exterior Size(W*L*H)(mm)	735*835*1115
--Packing Size(W*L*H)(mm)	857*885*1287
--Volume	230L
--Max. Shelf Number	17

--Load Per rack	15kg
--Shelf Space	40mm
--Power Rating (50/60Hz)	AC220V/13.6A
--NW/GW (kg)	94/120
Accessory	
--Shelf	2
--Shelf Frame	4
Optional accessories	Spare shelf, RS485 interface, printer, Program controller, U-disk storage; 4.3 inch color touch screen temperature controller.
Alt Name	Hot Air Sterilizing Drying Oven



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com