



NATURAL CONVECTION OVEN BER1M2

NATURAL CONVECTION OVEN BER1M2

DESKTOP CONSTANT-TEMPERATURE DRYING OVEN/ INCUBATOR



1. In the workroom, the hot air is convective naturally and cyclically.
2. Digital display microcomputer intelligent PID temperature controller.
3. New anti-hot handle.

SPECIFICATIONS

Model	BER1M2
Cycle Mode	Natural Convection
Function	
--Temp. Range	RT+10-300°C
--Temp. Resolution Ratio	0.1°C
--Temp. Motion	±1°C
--Temp. Uniformity	±3.5%
Structure	
--Inner Chamber	mirror stainless steel;
--Quter Shell	
--Insulation Layer	
--Heater	
--Power Rating	0.6kW
--Exhaust Hole	Φ35mm top (with function of test hole)
Controller	
--Temp. Control Mode	Two temperature section intelligent PID
--Temp. Setting Mode	Touch button setting
--Temp. Display Mode	Measuring temperature: display on upper row;Setting temperature:display on the lower row
--Timer	0-9999min(with timing wait function)
--Operation Function	fixed temperature operation, timing function, auto stop
--Additional Function	Sensor deviation correction, temperature overshoot self-tuning, internal parameter locking, power-off parameter memory
--Sensor	PT100
Safety Device	over temperature sound-light alarm
Specification	
--Inner Chamber size(W*L*H)(mm)	260*260*260
--Exterior Size (W*L*H)(mm)	380*455*568
--Packing Size (W*L*H)(mm)	515*480*640
--Volume	18L
--Max. Shelf Number	6

--Load Per rack	15kg
--Shelf Space	29mm
--Power Rating (50/60HZ)	AC220V/2.7A
--NW/GW (kg)	15/22
Accessory	
--Shelf	2
Optional accessories	Shelf
Alt Name	Desktop Constant-temperature Drying Oven/ Incubator



APPLICATIONS

Light natural convection drying oven / incubator.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com