



LABORATORY LOW SPEED CENTRIFUGE BET-1001

LABORATORY LOW SPEED CENTRIFUGE BET-1001

BENCHTOP LOW SPEED CENTRIFUGE



- The new XIUI3.0 OS features microcomputer control, programmable operations, and direct drive by a maintenance-free high-torque DC brushless motor for stable running.
- A 7" wide-angle LCD touch screen is for digital input and simple to operate. It can display set and run parameters in real time. It comes with an atmosphere light with seven colors available for enhancing the user experience. The all-steel housing is treated with corrosion-resistant orange peel fine wrinkles showing full lines, featuring an industrial human-machine design that shows a sense of safety while being visually appealing, and allowing a high recognition rate.
- They feature multiple audio/visual early warning protection functions for overspeed, over temperature, imbalance, wrong operation, overcurrent, overvoltage, and anti-pinch. The fluorosilicone rubber sealing ring, resistant to hydrogen, oil

SPECIFICATIONS

Model	BET-1001
Max capacity	4x250ml
Max speed	5,500r/min
Max RCF	4,800xg
Speed accuracy	±20r/min (customizable, multiples of 10)
Control and drive system	Microcomputer control, maintenance-free large-torque DC brushless motor
Display mode	7" wide-angle LCD touch screen
Operation mode	Touch control (with local control option)
Gears up/down	10 gears
Timer range	1s-99h59min59s, with continuous centrifugation and instantaneous centrifugation
Total power	0.45kW
Noise	≤65dB(A)
Power supply	AC220V 50Hz
Weight	40.5kg
Dimensions (LxWxH)	450mmx565mmx365mm
Alt Name	Benchtop Low Speed Centrifuge

ACCESSORIES FOR PURCHASE

No	Name	Description
1	Fixed-angle Rotor 12 x 10 mL through-hole rotor	Max RPM: 5,500r/min Max RCF: 3,120xg
2	Fixed-angle Rotor 12x15mL through-hole rotor	Max RPM: 5,500r/min Max RCF: 3,360xg
3	Swing-out rotor 4x250ml	Max RPM: 4,000r/min Max RCF: 2,848xg
4	Microplate Rotor 2x2x96 holes	Max RPM: 4,000r/min Max RCF: 2,368xg
5	Cytosmear rotor 48 slots	Max RPM: 2,000r/min Max RCF: 772xg
6	Swing-out rotor	Max RPM: 5,000r/min Max RCF: 4,800xg

7	Tube rack 5mL (ordinary tube)	Number of centrifuges: 5mLx48 holes Max RPM: 4,000r/min Max RCF: 2,368xg
8	Tube rack 5mL (blood collection tube)	Number of centrifuges: 5mLx48 holes Max RPM: 4,000r/min Max RCF: 2,832xg
9	Tube rack 15mL	Number of centrifuges: 15mLx16 holes Max RPM: 4,000r/min Max RCF: 2,960xg
10	Tube rack 15mL	Number of centrifuges: 15mLx24 holes Max RPM: 4,000r/min Max RCF: 2,960xg
11	Tube rack 15mL	Number of centrifuges: 15mLx32 holes Max RPM: 4,000r/min Max RCF: 2,960xg
12	Tube rack 50mL	Number of centrifuges: 50mLx4 holes Max RPM: 5,000r/min Max RCF: 4,625xg
13	Tube rack 50mL	Number of centrifuges: 50mLx8 holes Max RPM: 4,000r/min Max RCF: 2,960xg
14	Tube rack 100mL	Number of centrifuges: 100mLx4 holes Max RPM: 5,000r/min Max RCF: 4,800xg
15	Tube rack 100mL	Number of centrifuges: 100mLx8 holes Max RPM: 4,000r/min Max RCF: 3,072xg



1



2



3



4




5



6



7



8



9



10



11



12



13



14



15

FEATURES

- The new XIUI3.0 OS features microcomputer control, programmable operations, and direct drive by a maintenance-free high-torque DC brushless motor for stable running.

- A 7" wide-angle LCD touch screen is for digital input and simple to operate. It can display set and run parameters in real time. It comes with an atmosphere light with seven colors available for enhancing the user experience. The all-steel housing is treated with corrosion-resistant orange peel fine wrinkles showing full lines, featuring an industrial human-machine design that shows a sense of safety while being visually appealing, and allowing a high recognition rate.
- They feature multiple audio/visual early warning protection functions for overspeed, over temperature, imbalance, wrong operation, overcurrent, overvoltage, and anti-pinch. The fluorosilicone rubber sealing ring, resistant to hydrogen, oil, acids and alkalis, is capable of long-time use at the temperature. from -55°C to +200°C. The aesthetically pleasing and hermetically thermoformed inner panel of the cabin door can dually prevent aerosol spillage. The 304 stainless steel seamless corrosion-resistant centrifuge chamber and steel cylinder sleeve are designed with a sound-absorbing air duct.
- The door cover has an electronic lock allowing for one-button opening. The gas spring hydraulic rod makes it easy and convenient for the door cover to close. In case of shutdown or power outage, the cover can be manually opened. The patented anti-pinch function can prevent injuring fingers by hasty operations.
- The Bluetooth and Type C interfaces are optional for short-range control via mini-programs, facilitating system upgrades and experimental data downloads.
- There are 10 gears for acceleration/deceleration and three-stage damping for shock absorption, ensuring stable sample operation without resuspension. They can store 99 groups of programs, with parameters modifiable during operation without the need to stop, and current parameters being automatically saved. They can be programmable according to user needs for point control, timing, differential timing, density, and gradient centrifugation functions, thus meeting diverse experimental requirements.
- Paired with forged aerospace aluminum rotors (fix-angle rotors only) and a variety of optional polyamide fiber adapters, the centrifuges are suitable for 0.2mL to 250mL centrifuge tubes or reagent bottles and are able to centrifugate all types of MTP microplates, PCR plates, cell culture plates and deep well plates.
- These products are supported by certifications including ISO 9001 (2015); ISO 13485 (2016); ISO 14001 (2015);

APPLICATIONS

Favored by our customers, this is one of the best-selling models of Herexi Instrument. Paired with a variety of buckets and adapters, they are ideal for clinical testing and laboratory analysis. They are widely used in experiments and scientific research in the fields of biology, chemistry, medicine, agriculture and forestry, food safety, blood stations, clinical trials, etc.

MORE INFO

Customizable per customer needs

Tube rack	Adapter
10mL	1x1.5/2mL, 1x5mL
15mL	1x1.5/2mL, 1x5mL, 1x10mL
50mL	3x1.5/2mL, 1x5mL, 1x10mL, 1x10mL, 1x15mL, 1x20mL, 1x30mL
100mL	3x1.5/2mL, 4x5mL, 1x50mL
250mL	12x1.5/2mL, 9x5mL, 7x10mL, 1x50mL, 1x100mL



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
 Email: info@biolabscientific.com | Website: www.biolabscientific.com