



LABORATORY LOW SPEED CENTRIFUGE BET-901

LABORATORY LOW SPEED CENTRIFUGE BET-901

BENCHTOP LOW SPEED LARGE CAPACITY CENTRIFUGE



- The new XIUI3.0 OS features microcomputer control, programmable operations, and direct drive by a variable frequency brushless motor for precise speed control.
- A 7" wide-angle LCD touch screen is for digital input and simple to operate. It can display set and run parameters in real time. It comes with an atmosphere light with seven colors available for enhancing the user experience. The all-steel housing is treated with corrosion-resistant orange peel fine wrinkles showing full lines, featuring an industrial human-machine design that shows a sense of safety while being visually appealing, and allowing a high recognition rate.
- They feature multiple audio/visual early warning protection functions for overspeed, over temperature, imbalance, wrong operation, overcurrent, overvoltage, a

SPECIFICATIONS

| | |
|--------------------------|---|
| Model | BET-901 |
| Max capacity | 4x750ml |
| Max speed | 5,500r/min |
| Max RCF | 4,800xg |
| Speed accuracy | ±20r/min (customizable, multiples of 10) |
| Control and drive system | Microcomputer control, maintenance-free large-torque inverter brushless motor |
| Display mode | 7" wide-angle LCD touch screen |
| Operation mode | Touch control (local control optional) |
| Gears up/down | 10 gears |
| Timer range | 1s-99h59min59s, with continuous centrifugation and instantaneous centrifugation |
| Total power | 0.85kW |
| Noise | ≤65dB(A) |
| Power supply | AC220V 50Hz |
| Weight | 63.5kg |
| Dimensions (LxWxH) | 510mmx610mmx405mm |
| Alt Name | Benchtop Low Speed Large Capacity Centrifuge |

ACCESSORIES FOR PURCHASE

| No | Name | Description |
|----|----------------------------------|---|
| 1 | Fixed-angle Rotor 12x10mL | Max RPM: 5,000r/min Max RCF: 2,600xg |
| 2 | Fixed-angle Rotor 12x15mL | Max RPM: 5,000r/min Max RCF: 2,800xg |
| 3 | Fixed-angle Rotor 4x500ml | Max RPM: 4,000r/min Max RCF: 3,360xg |
| 4 | Microplate rotor 2x2x96 holes | Max RPM: 4,000r/min Max RCF: 2,368xg |
| 5 | Swing-out rotor | Max RPM: 5,000r/min Max RCF: 4,800xg |
| 6 | Tube rack 5mL (ordinary tube) | Number of centrifuges: 5mLx48 holes Max RPM: 4,000r/min Max RCF: 2,368xg |

| | | |
|----|--|--|
| 7 | Tube rack 5mL (blood collection tube) | Number of centrifuges: 5mLx48 holes Max RPM: 4,000r/min Max RCF: 2,832xg |
| 8 | Tube rack 15mL | Number of centrifuges: 15mLx16 holes Max RPM: 4,000r/min Max RCF: 2,960xg |
| 9 | Tube rack 15mL | Number of centrifuges: 15mLx24 holes Max RPM: 4,000r/min Max RCF: 2,960xg |
| 10 | Tube rack 15mL | Number of centrifuges: 15mLx32 holes Max RPM: 4,000r/min Max RCF: 2,960xg |
| 11 | Tube rack 50mL | Number of centrifuges: 50mLx4 holes Max RPM: 5,000r/min Max RCF: 4,625xg |
| 12 | Tube rack 50mL | Number of centrifuges: 50mLx8 holes Max RPM: 4,000r/min Max RCF: 2,960xg |
| 13 | Tube rack 100mL | Number of centrifuges: 100mLx4 holes Max RPM: 5,000r/min Max RCF: 4,800xg |
| 14 | Tube rack 100mL | Number of centrifuges: 100mLx8 holes Max RPM: 4,000r/min Max RCF: 3,072xg |
| 15 | Swing-out rotor | Max RPM: 4,000r/min Max RCF: 3,024xg |
| 16 | Tube rack 5mL (blood collection tube) | Number of centrifuges: 5mLx76 holes Max RPM: 4,000r/min Max RCF: 3,024xg |
| 17 | Tube rack 250mL (flat bottom) | Number of centrifuges: 250mLx4 holes Max RPM: 4,000r/min Max RCF: 2,848xg |
| 18 | Swing-out rotor | Max RPM: 4,000r/min Max RCF: 3,024xg |
| 19 | Tube rack 5mL (blood collection tube) | Number of centrifuges: 5mLx124 holes Max RPM: 4,000r/min Max RCF: 3,584xg |
| 20 | Tube rack 750mL | Number of centrifuges: 750mLx4 holes Max RPM: 4,000r/min Max RCF: 3,536xg |



1



2



3




4



5



6



FEATURES

- The new XIUI3.0 OS features microcomputer control, programmable operations, and direct drive by a variable frequency brushless motor for precise speed control.
- A 7' wide-angle LCD touch screen is for digital input and simple to operate. It can display set and run parameters in real time. It comes with an atmosphere light with seven colors available for enhancing the user experience. The all-steel housing is treated with corrosion-resistant orange peel fine wrinkles showing full lines, featuring an industrial human-machine design that shows a sense of safety while being visually appealing, and allowing a high recognition rate.
- They feature multiple audio/visual early warning protection functions for overspeed, over temperature, imbalance, wrong operation, overcurrent, overvoltage, and anti-pinch. The fluorosilicone rubber sealing ring, resistant to hydrogen, oil, acids and alkalis, is capable of long-time use at the temperature from -55°C to +200°C. The aesthetically pleasing and hermetically thermoformed inner panel of the cabin door can dually prevent aerosol spillage. The 304 stainless steel seamless corrosion-resistant centrifuge chamber and steel cylinder sleeve are designed with a sound-absorbing air duct.
- The door cover has an electronic lock allowing for one-button opening. The gas spring hydraulic rod makes it easy and convenient for the door cover to close. In case of shutdown or power outage, the door cover can be manually opened. The patented anti-pinch function can prevent injuring fingers by hasty operations.
- The Bluetooth and Type C interfaces are optional for short-range control via mini-programs, facilitating system upgrades and experimental data downloads.
- There are 10 gears for acceleration/deceleration and three-stage damping for shock absorption, ensuring stable sample operation without resuspension. They can store 99 groups of programs, with parameters modifiable during operation without the need to stop, and current parameters being automatically saved. They can be programmable according to user needs for point control, timing, differential timing, density, and gradient centrifugation functions, thus meeting diverse experimental requirements.
- Paired with forged aerospace aluminum rotors (fix-angle rotors only) and a variety of optional polyamide fiber adapters, the centrifuges are suitable for 0.2mL to 750mL centrifuge tubes or reagent bottles and are able to centrifugate all types of MTP microplates, PCR plates, cell culture plates and deep well plates.
- These products are supported by certifications including ISO 9001 (2015); ISO 13485 (2016); ISO 14001 (2015); ISO 45001 (2018); and CFDA registration and production qualification.

APPLICATIONS

The benchtop low speed large capacity centrifuge is suitable for centrifuging various micro samples, and has many other applications, including academic research, medical institutions, biopharmaceuticals, agricultural research, and lab experiments at universities, offering an excellent cost-performance ratio.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com