



LABORATORY LOW SPEED CENTRIFUGE BET1BI1

LABORATORY LOW SPEED CENTRIFUGE BET1BI1

OIL CENTRIFUGE

Designed in line with the Test Method for Water and Sediment in Crude Oil by the Centrifuge Method (GB/T6533-2012), this centrifuge is an ideal moisture determination instrument for the oil exploitation industry and R&D institutions, which measures the water and sediment in crude oil by the centrifuge method.



SPECIFICATIONS

Model	BET1BI1
Max RCF	2,960xg
Max speed	4,000r/min
Speed accuracy	±30r/min (customizable, multiples of 10)
Motor	High torque variable frequency AC/DC motor, microcomputer control
Temperature control range	
Temperature control accuracy	
Timer range	1min~99h59min59s, with continuous centrifugation and instantaneous centrifugation
Power supply	AC220V50Hz
Noise	≤60dB(A)
Weight	50kg
Dimensions (L x W x H)	450mmx590mmx365mm
Alt Name	Oil Centrifuge

ACCESSORIES FOR PURCHASE

No	Name	Description
1	24x15mL	Max RPM: 4,000r/min Max RCF: 2,960xg



1



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com