



LABORATORY LOW SPEED CENTRIFUGE BET1BN1

LABORATORY LOW SPEED CENTRIFUGE BET1BN1

PORTABLE CENTRIFUGE

It can better satisfy field-testing requirements in the open air, such as: Determination of total phosphorus in surface water, material analysis, food safety inspection, clinical examinations, academic research and other scientific demands in various other areas. Conforming to HJ91.2-2022 "Technical specification for surface water environmental quality monitoring", it can also customize rotor on demand.



- Supported by the dual-mode operations, it can be controlled both by a WeChat Mini Program to address the issue of nearby operation in a high-risk environment, and by the instrument panel.
- Data acquisition and monitoring can be automatically executed during spinning.
- With microcomputers, self-developed control boards and high-torque AC/DC brushless motors, these concentrators can run stably with low noise, allowing for a comfortable laboratory environment;
- It has the multiple alarm functions for over speed, over temperature, over pressure, imbalance and under pressure;
- The integrated design is portable, enabling pretreatment before use on site;
- Characterized by strong endurance and long durability, it can run continuously for more than 8 hours (at the temperature of 20°C and the humidity of 75%);

SPECIFICATIONS

Model	BET1BN1
Portable centrifuge Max RPM	4000r/min (customizable)
Max RCF	2578xg (customizable)
Max capacity	4x250ml (customizable)
Timer range	1min~23h59min59s
Power supply	AC220V50Hz
Total power	350W
Noise	≤40dB
Weight	28kg
Dimensions (LxWxH)	580mmx440mmx285mm
Alt Name	Portable Centrifuge



FEATURES

- Supported by the dual-mode operations, it can be controlled both by a WeChat Mini Program to address the issue of nearby operation in a high-risk environment, and by the instrument panel.
- Data acquisition and monitoring can be automatically executed during spinning.
- With microcomputers, self-developed control boards and high-torque AC/DC brushless motors, these concentrators can run stably with low noise, allowing for a comfortable laboratory environment;
- It has the multiple alarm functions for over speed, over temperature, over pressure, imbalance and under pressure;
- The integrated design is portable, enabling pretreatment before use on site;
- Characterized by strong endurance and long durability, it can run continuously for more than 8 hours (at the temperature of 20°C and the humidity of 75%);
- It is easy to operate and error-proof (the centrifuge cannot be started when the cover isn't closed).

- The centrifugal chambers are made of alloy aluminum that has undergone an anodic electrophoresis surface treatment and thus can be resistant to most chemical reagents and solvents.
- CFDA registration and production qualification, with ISO 9001 (2015) and ISO 13485 (2016) certifications.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com