



## LABORATORY HIGH SPEED CENTRIFUGE BET1P2

# LABORATORY HIGH SPEED CENTRIFUGE BET1P2

## HIGH SPEED REFRIGERATED CENTRIFUGES



- Mitsubishi PLC, Weinview touch screen and a high-torque variable frequency AC motor are used to ensure the stable operation with low noise and create a comfortable laboratory environment.
- Imported fluorine-free refrigeration compressor unit and eco-friendly refrigerant R404a, allowing for a wide temperature control range: -20°C to + 40°C (can be set during operation); pre-cooling function (quickly cool down to the set temperature); standby cooling function (maintain the set temperature in the standby state); heating and defrosting function.
- Early warning functions such as overspeed, overheating, imbalance, undervoltage, and overvoltage warnings; three-stage damping shock absorber, a specially combined shock absorbing device to ensure the motor runs smoothly and safely and prevent samples from resuspending, thus securing excellent centrifugal effect.

## SPECIFICATIONS

Model	BET1P2
Max capacity	4x1,000mL
Max speed	21,000r/min
Max RCF	53,741xg
Speed accuracy	±30r/min (customizable, multiples of 10)
Refrigeration system	Imported fluorine-free refrigeration compressor unit and eco-friendly refrigerant R404a
Temperature control range	-20°C~+40°C
Temperature control accuracy	±1°C
Number of running programs	16
Control and drive system	High torque variable frequency AC motor, microcomputer control
Timer range	1min~99h59min59s, with continuous centrifugation and instantaneous centrifugation
Rotor recognition	Auto rotor identification
Noise	≤65dB(A)
Total power	4.0kW
Weight	240kg
Dimensions (LxWxH)	710mmx910mmx950mm
Alt Name	High Speed Refrigerated Centrifuges

## ACCESSORIES FOR PURCHASE

No	Name	Description
1	Fixed-angle Rotor 30x1.5mL	Max RPM: 21,000r/min Max RCF: 53,741xg
2	Fixed-angle Rotor 16x10 mL	Max RPM: 21,000r/min Max RCF: 48811xg
3	Fixed-angle Rotor 20x15mL (conical-bottom)	Max RPM: 14,000r/min Max RCF: 26295xg
4	Fixed-angle Rotor 6x50ml (conical-bottom)	Max RPM: 20,000r/min Max RCF: 41,589xg
5	Fixed-angle Rotor 6x50mL (round-bottom)	Max RPM: 21,000r/min Max RCF: 46,346xg
6	Fixed-angle Rotor 8x50mL (round-bottom)	Max RPM: 16,000r/min Max RCF: 28,048xg

7	Fixed-angle Rotor 8x50ml (conical-bottom)	Max RPM: 16,000r/min Max RCF: 30,052xg
8	Fixed-angle Rotor 8x100mL (round-bottom)	Max RPM: 14,000r/min Max RCF: 25,637xg
9	Fixed-angle Rotor 6x250mL	Max RPM: 13,000r/min Max RCF: 25,508xg
10	Fixed-angle Rotor 6x500mL	Max RPM: 8,000r/min Max RCF: 11,377xg
11	Fixed-angle Rotor 6x500mL (imported bottle)	Max RPM: 10,000r/min Max RCF: 17,776xg
12	Cable fiber fixed-angle rotor 6x500mL (imported bottle)	Max RPM: 11,000r/min Max RCF: 21509xg
13	Fixed-angle Rotor 4x1,000mL	Max RPM: 8,000r/min Max RCF: 12,594xg
14	Continuous flow rotor 1000mL	Max RPM: 14,000r/min Max RCF: 21,475xg
15	Continuous flow rotor 3000mL	Max RPM: 8,000r/min Max RCF: 9,445xg
16	Swing-out rotor 4x750ml	Max RPM: 4,000r/min Max RCF: 3,536xg
17	Microplate Rotor 4x2x96 holes	Max RPM: 4,000r/min Max RCF: 3166xg



## FEATURES

- Mitsubishi PLC, Weinview touch screen and a high-torque variable frequency AC motor are used to ensure the stable operation with low noise and create a comfortable laboratory environment.
- Imported fluorine-free refrigeration compressor unit and eco-friendly refrigerant R404a, allowing for a wide temperature control range: -20°C to + 40°C (can be set during operation); pre-cooling function (quickly cool down to the set temperature); standby cooling function (maintain the set temperature in the standby state); heating and defrosting function.
- Early warning functions such as overspeed, overheating, imbalance, undervoltage, and overvoltage warnings; three-stage damping shock absorber, a specially combined shock absorbing device to ensure the motor runs smoothly and safely and prevent samples from resuspending, thus securing excellent centrifugal effect.
- Touch control mode for displaying both the set parameters and running parameters, with an intuitive, simple, and easy-to-use interface; operation menu in multiple languages.
- Biosafety air-tight fix-angle rotor adopting an integral silicone rubber sealing ring (EU RoHS 2015/863) to avoid aerosol overflow and fully ensure the safety of operators and lab environments.
- Stainless steel centrifugal chamber equipped with an all-steel plastic-sprayed housing, integrally formed stamping steel front cover, and a three-layer steel protective cover, which is sturdy and durable to ensure the safety of operators and labs.
- Easy-to-use mechanical locks suitable for various harsh environments (gently close the door, and the locking system will be triggered to lock the door securely).
- 12 levels speed-up and speed-down control; storage of up to 16 sets of user-defined programs; modification of control parameters of the running rotor at any time; display of speed rise and fall curve, centrifugal integral curve, and temperature curve.

- Multi-specification forged aerospace aluminum rotors (fix-angle rotors only) and a variety of optional polyamide fiber adapters, suitable for 1.5mL to 1,000mL centrifuge tubes or reagent bottles.
- Casters and carbon steel caster adjustment blocks at the bottom for easy movement and level adjustment of the device.
- CFDA registration and production qualification, with ISO 9001 (2015) and ISO 13485 (2016) certifications.



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada  
Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)