



LABORATORY HIGH SPEED REFRIGERATED CENTRIFUGE BET1R3

LABORATORY HIGH SPEED REFRIGERATED CENTRIFUGE

BET1R3

INTELLIGENT HIGH SPEED REFRIGERATED CENTRIFUGE



- With single-chip microcomputers, self-developed control boards and high-torque AC/DC brushless motors, these concentrators can run stably with lower noise, allowing for a comfortable laboratory environment.
- Imported fluorine-free refrigeration compressor unit and eco-friendly refrigerant R404a, allowing for a wide temperature control range: -20°C to +40°C (can be set during operation); pre-cooling function (quickly cool down to the set temperature); standby cooling function (maintain the set temperature in the standby state); heating and defrosting function.
- Early warning functions such as overspeed, overheating, imbalance, undervoltage, and overvoltage warnings; three-stage damping shock absorber, a specially combined shock absorbing device to ensure the motor runs smoothly and safely and prevent samples from resuspending, thus securing excellent centrifugal effect.

SPECIFICATIONS

Model	BET1R3
Max speed	16,800r/min
Max RCF	20,320xg
Standard rotor	12x1.5/2.0ml
Max capacity	4x100ml
Speed accuracy	±30r/min (customizable, multiples of 10)
Refrigeration system	Imported fluorine-free refrigeration compressor unit and eco-friendly refrigerant R404a
Control and drive system	High torque AC/DC brushless motor, microcomputer control
Temperature control range	-20°C~+40°C
Temperature control accuracy	±1°C
Number of running programs	100
Total power	1.5kW
Timer range	1min~99h59min59s, with continuous centrifugation and instantaneous centrifugation
Noise	≤65dB(A)
Rotor recognition	Auto rotor identification
Weight	75kg
Dimensions (LxWxH)	710mmx630mmx370mm
Alt Name	Intelligent High Speed Refrigerated Centrifuge

ACCESSORIES FOR PURCHASE

No	Name	Description
1	Fixed-angle Rotor 12x1.5/2.0ml	Max RPM: 16,800r/min Max RCF: 20,320xg
2	Fixed-angle Rotor 12x1.5mL	Max RPM: 16,800r/min Max RCF: 20,320xg Bio-isolated rotor cover

3	Fixed-angle Rotor 24x1.5/2.0ml	Max RPM: 14,000r/min Max RCF: 19,600xg Bio-isolated rotor cover
4	Fixed-angle Rotor 48x1.5mL	Max RPM: 13,000r/min Max RCF: 18,750xg
5	Fixed-angle Rotor 12x5mL	Max RPM: 14,000r/min Max RCF: 15,090xg
6	Fixed-angle Rotor 12x10mL	Max RPM: 12,000r/min Max RCF: 14,540xg Bio-isolated rotor cover
7	Fixed-angle Rotor 12x15 ml/10ml (through-holes)	Max RPM: 6,000r/min Max RCF: 3,740xg
8	Fixed-angle Rotor 8x15ml (conical-bottom)	Max RPM: 12,000r/min Max RCF: 15,840xg Bio-isolated rotor cover
9	Fixed-angle Rotor 8x15ml (round-bottom)	Max RPM: 12,000r/min Max RCF: 15,400xg Bio-isolated rotor cover
10	Fixed-angle Rotor 6x50ml	Max RPM: 11,000r/min Max RCF: 14,640xg Bio-isolated rotor cover Optional conical-to-round adapter
11	Fixed-angle Rotor 6x50ml (through-holes)	Max RPM: 6,000r/min Max RCF: 3,670xg
12	Fixed-angle Rotor 4x100ml (round-bottom)	Max RPM: 9,000r/min Max RCF: 9,230xg Bio-isolated rotor cover
13	Swing-out rotor 4x50ml	Max RPM: 4,000r/min Max RCF: 2,650xg
14	Swing-out rotor 4x100ml	Max RPM: 4,000r/min Max RCF: 2,460xg
15	Microplate Rotor 2x2x48 holes	Max RPM: 3,000r/min Max RCF: 1,120xg



1



2



3



4



5



6



7



8



9



10



11



12



13



14



15

FEATURES

- With single-chip microcomputers, self-developed control boards and high-torque AC/DC brushless motors, these concentrators can run stably with lower noise, allowing for a comfortable laboratory environment.
- Imported fluorine-free refrigeration compressor unit and eco-friendly refrigerant R404a, allowing for a wide temperature control range: -20°C to +40°C (can be set during operation); pre-cooling function (quickly cool down to the set temperature); standby cooling function (maintain the set temperature in the standby state); heating and defrosting function.
- Early warning functions such as overspeed, overheating, imbalance, undervoltage, and overvoltage warnings; three-stage damping shock absorber, a specially combined shock absorbing device to ensure the motor runs smoothly and safely and prevent samples from resuspending, thus securing excellent centrifugal effect.
- TFT-LCD true color display screen, dual operation modes of touch screen and physical keys, and special keys for centrifugal force display, display of the set parameters and operating parameters at the same time, modification of parameters at any time during operation without interruption; intuitive, simple, and easy-to-use interface; operation menu in multiple languages
- Biosafety air-tight fix-angle rotor adopting an integral silicone rubber sealing ring (EU RoHS 2015/863) to avoid aerosol overflow and fully ensure the safety of operators and lab environments.
- Stainless steel centrifugal chamber at the rear equipped with an all-steel plastic-sprayed housing, integrally formed stamping steel front cover, and a three-layer steel protective cover, which is sturdy and durable to ensure the safety of operators and labs.
- Exquisite industrial appearance design with a novel and artistic diamond shape, more suitable for placement in the corner, saving the limited bench space of labs.
- Silent, easy-to-use mechatronics motor door lock (gently close the door, and the locking system will be triggered to lock the door securely).
- 10 levels speed-up and speed-down control; storage of up to 100 sets of user-defined programs; easy calling of frequently used programs (the last used programs are called when the device is powered on).
- Multi-specification forged aerospace aluminum rotors (fix-angle rotors only) and a variety of optional polyamide fiber adapters, suitable for 0.2mL to 100mL centrifuge tubes or reagent bottles; able to centrifuge all types of MTP microplates, PCR plates, and cell culture plates.
- CFDA registration and production qualification, with ISO 9001 (2015) and ISO 13485 (2016) certifications.

APPLICATIONS

With a variety of optional fix-angle rotors and swing-out rotors and up to 100 sets of custom programs. This centrifuges that are extraordinarily versatile. They are used for bacteria and protein precipitation, nucleic acid extraction, cell/subcellular fractionation, and environmental sample processing.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com