



MICRO CENTRIFUGE BET2H1

MICRO CENTRIFUGE BET2H1

MICRO HIGH SPEED CENTRIFUGE



- The new XIUI3.0 OS features microcomputer control, programmable operations, and direct drive by a maintenance-free high-torque DC brushless motor for stable running.
- A 7" wide-angle LCD touch screen is for digital input and simple to operate. It can display set and run parameters in real time. It comes with an atmosphere light with seven colors available for enhancing the user experience. The all-steel housing is treated with corrosion-resistant orange peel fine wrinkles showing full lines, featuring an industrial human-machine design that shows a sense of safety while being visually appealing, and allowing a high recognition rate.
- They feature multiple audio/visual early warning protection functions for overspeed, over temperature, imbalance, wrong operation, overcurrent, overvoltage, and anti-pinch. The fluorosilicone rubber sealing ring, resistant to hydrogen, oil

SPECIFICATIONS

Model	BET2H1
Max capacity	12x10mL
Max speed	16,500r/min
Max RCF	25,500xg
Speed accuracy	±20r/min (customizable, multiples of 10)
Control and drive system	Microcomputer control, maintenance-free large-torque DC brushless motor
Display mode	7" wide-angle LCD touch screen
Operation mode	Touch control (with local control option)
Rotor recognition	Automated loading and locking of rotor parameters (optional)
Gears up/down	10 gears
Timer range	1s-99h59min59s, with continuous centrifugation and instantaneous centrifugation
Total power	0.35kW
Noise	≤65dB(A)
Power supply	AC220V 50Hz
Weight	17.5kg
Dimensions (LxWxH)	260mmx390mmx305mm
Alt Name	Micro High Speed Centrifuge

ACCESSORIES FOR PURCHASE

No	Name	Description
1	Fixed-angle Rotor 12x1.5mL	Max RPM: 16,500r/min Max RCF: 19856xg
2	Fixed-angle Rotor 24x1.5mL	Max RPM: 15,000r/min Max RCF: 22,500xg
3	Fixed-angle Rotor 48x1.5mL	Max RPM: 14,000r/min Max RCF: 21756xg
4	Fixed-angle Rotor 10x5mL	Max RPM: 14,000r/min Max RCF: 14308xg
5	Fixed-angle Rotor 12x5mL	Max RPM: 13,500r/min Max RCF: 14,033xg
6	Fixed-angle Rotor 8x7mL	Max RPM: 14,000r/min Max RCF: 14112xg

7	Fixed-angle Rotor 12x10mL	Max RPM: 12,000r/min Max RCF: 14544xg
8	Fixed-angle Rotor 4x8x0.2mL (12x5mL PCR 8-tube strings)	Max RPM: 14,000r/min Max RCF: 15288xg



FEATURES

- The new XIUI3.0 OS features microcomputer control, programmable operations, and direct drive by a maintenance-free high-torque DC brushless motor for stable running.
- A 7" wide-angle LCD touch screen is for digital input and simple to operate. It can display set and run parameters in real time. It comes with an atmosphere light with seven colors available for enhancing the user experience. The all-steel housing is treated with corrosion-resistant orange peel fine wrinkles showing full lines, featuring an industrial human-machine design that shows a sense of safety while being visually appealing, and allowing a high recognition rate.
- They feature multiple audio/visual early warning protection functions for overspeed, over temperature, imbalance, wrong operation, overcurrent, overvoltage, and anti-pinch. The fluorosilicone rubber sealing ring, resistant to hydrogen, oil, acids and alkalis, is capable of long-time use at the temperature from -55°C to +200°C. The aesthetically pleasing and hermetically compression-molded inner panel of the cabin door can dually prevent aerosol spillage. The 304 stainless steel seamless corrosion-resistant centrifuge chamber and steel cylinder sleeve are designed with a sound-absorbing air duct.
- The door cover has an electronic lock allowing for one-button opening. The door cover can be locked automatically by gently closing it. In case of shutdown or power outage, the door cover can be manually opened.
- The Bluetooth/Type C interfaces are optional for short-range control via mini-programs, facilitating system upgrades and experimental data downloads.
- There are 10 gears for acceleration/deceleration and three-stage damping for shock absorption, ensuring stable sample operation without resuspension. They can store 99 groups of programs and be programmable according to user needs for point control, timing, differential timing, density, and gradient centrifugation functions, thus meeting diverse experimental requirements.
- The optional rotor has an auto recognition function and can automatically load and lock rotor parameters; parameters may be modified during operation without the need to stop, and current parameters may be automatically saved.
- Forged aerospace aluminum rotors, suitable for centrifuge tubes of 0.2ml to 2.0ml, paired with PCR 8-tube strips.
- These products are supported by certifications including ISO 9001 (2015); ISO 13485 (2016); ISO 14001 (2015); ISO 45001 (2018); and CFDA registration and production qualification.

APPLICATIONS

This instrument is mainly used for rapid precipitation and separation of DNAs, RNAs, proteins and viruses, with application in bacteria and protein precipitation, nucleic acid extraction, cell/subcellular component separation, environmental sample processing, clinical trial sample processing, etc.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com