



LABORATORY LOW SPEED CENTRIFUGE BEW-1201

LABORATORY LOW SPEED CENTRIFUGE BEW-1201

TABLETOP LOW-SPEED CENTRIFUGE



SPECIFICATIONS

Model	BEW-1201
Max speed	4000r/min
Max RCF	2500xg
Max capacity	6x50ml
Speed accuracy	±30r/min
Time setting	1s~99min59s
Noise	<60dB (A)
Power supply	AC110V/AC220V, 50Hz~60Hz
Consumption	150W
Dimension (LxWxH)	330mmx420mmx280mm
Packing size (LxWxH)	430mmx520mmx390mm
Net weight (No rotor)	14kg
Alt Name	Tabletop Low-Speed Centrifuge

ACCESSORIES FOR PURCHASE

No	Name	Description
1	Angle Rotor	Capacity: 12x7 ml Max Speed: 4000 r/min Max RCF: 2220 xg
2	Angle Rotor	Capacity: 18x7 ml Max Speed: 4000 r/min Max RCF: 2220 xg
3	Angle Rotor	Capacity: 24x7 ml Max Speed: 4000 r/min Max RCF: 2220 xg
4	Angle Rotor	Capacity: 12x10 ml / 15 ml Max Speed: 4000 r/min Max RCF: 2220 xg Adaptor: 1.5 ml, 5 ml / 7 ml
5	Angle Rotor	Capacity: 18/24x10 ml Max Speed: 4000 r/min Max RCF: 2220 xg Adaptor: 1.5 ml, 5 ml / 7 ml

6	Angle Rotor	Capacity: 12x20 ml Max Speed: 4000 r/min Max RCF: 2220 xg Adaptor: 5 ml, 10 ml
7	Angle Rotor	Capacity: 6x50 ml Max Speed: 4000 r/min Max RCF: 2220 xg Adaptor: 15 ml, 20 ml
8	Swing rotor	Capacity: 8x15 ml Max Speed: 4000 r/min Max RCF: 2220 xg Rotor Angle: =90°
9	Swing rotor	Capacity: 8x15 ml Max Speed: 4000 r/min Max RCF: 2220 xg Rotor Angle: =60°
10	Swing rotor	Capacity: 4x50 ml Max Speed: 4000 r/min Max RCF: 2500 xg Rotor Angle: =60°



1



2



3



4



5



6



7



8



9



10



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com