



LABORATORY HIGH SPEED REFRIGERATED CENTRIFUGE BEW-802

LABORATORY HIGH SPEED REFRIGERATED CENTRIFUGE

BEW-802

FLOOR-STANDING HIGH-SPEED REFRIGERATED CENTRIFUGE



The max speed is 12000 rpm, and the largest capacity of fixed rotor is 4x2000 ml. It has micro-computer control, electronic lock and AC variable-conversion motor which delivers high torque.

Imported compressor unit with Non-CFC refrigerant R404a.

Automatic rotor recognition make safety for multiple rotors choice.

Up to 100 user programs storage.

It has self-locking, over-speed detection, over-temperature detection, imbalance detection that is automatic alarm device.

It has 10 levels acceleration and 11 levels deceleration to be setting according to the different requirement. Slow down freely is available.

Silastic sealed ring comfort to GMP, US FDA certificated.

SPECIFICATIONS

Model	BEW-802
Max speed	12000r/min
Max RCF	19830xg
Max capacity	4x2000ml
Speed accuracy	±10r/min
Time setting	1s~99h59min59s
Temperature setting	-20~+40°C
Temperature accuracy	±1°C
Compressor unit	French Tecumseh Compressor Unit R404a
Noise	<65dB (A)
Power supply	AC220V 50Hz 30A
Consumption	5.5kW
Alt Name	Floor-standing High-Speed Refrigerated Centrifuge

ACCESSORIES FOR PURCHASE

No	Name	Description
1	Angle Rotor	Capacity: 8x100 ml / 85 ml Max Speed: 12000 r/min Max RCF: 19830 xg Adaptor: 10 ml, 20 ml
2	Angle Rotor	Capacity: 6x1000 ml Max Speed: 7000 r/min Max RCF: 11600 xg Adaptor: 100 ml, 250 ml, 300 ml, 500 ml
3	Angle Rotor	Capacity: 4x2000 ml Max Speed: 6000 r/min Max RCF: 8410 xg Adaptor: 250 ml, 300 ml, 500 ml, 1000 ml
4	Angle Rotor	Capacity: 6x500 ml / 400 ml Max Speed: 8000 r/min Max RCF: 11620 xg Adaptor: 50 ml, 100 ml, 250 ml



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com