



LABORATORY LOW SPEED CENTRIFUGE BEW1K2 (BCBL-112)

LABORATORY LOW SPEED CENTRIFUGE BEW1K2

TABLETOP LOW-SPEED CENTRIFUGE



It has micro-computer control, electronic lock and DC brushless motor which is low noise and high speed accuracy.

Digital LCD screen make visualized operation conveniently.

Up to 9 user programs storage meet more demands.

It has self-locking, over-speed detection, over-temperature detection, imbalance detection that is automatic alarm device.

It has 9 levels acceleration and 10 levels deceleration to be setting according to the different requirement. Slow down freely is available.

Silastic sealed ring comfort to GMP, US FDA certificated.

SPECIFICATIONS

Model	BEW1K2
Old Model	BCBL-112
Max speed	5000r/min
Max RCF	4100xg
Max capacity	
Speed accuracy	±30r/min
Time setting	1min~99min59s
Noise	<65dB(A)
Power supply	AC110V/AC220V, 50Hz~60Hz
Consumption	250W
Dimension (LxWxH)	410mmx490mmx310mm
Packing size (LxWxH)	500mmx580mmx400mm
Net weight (No rotor)	25kg
Alt Name	Tabletop Low-Speed Centrifuge

ACCESSORIES FOR PURCHASE

No	Name	Description
1	Angle Rotor	Capacity: 12x15 ml Max Speed: 6000 r/min / 5000 r/min Max RCF: 5120 xg / 4100 xg
2	Angle Rotor	Capacity: 24x10 ml Max Speed: 6000 r/min / 5000 r/min Max RCF: 5120 xg / 4100 xg
3	Swing rotor	Capacity: 16x15 ml Max Speed: 4200 r/min Max RCF: 2760 xg Rotor Angle: =90°
4	Adaptor	4x4x15 ml 1.5, 5, 7, 10 ml
5	Swing rotor	Max Speed: 4200 r/min Max RCF: 2760 xg Rotor Angle: =60°
6	Adaptor	2x12x5 ml 5 ml / 7 ml
7	Adaptor	12x2x10 ml 0.5 ml, 1.5 ml, 5 ml / 7 ml

8	Adaptor	12x15 ml 0.5 ml, 5 ml, 10 ml, 5 ml / 7 ml
9	Swing rotor	Capacity: 4x50 ml Max Speed: 4200 r/min Max RCF: 2760 xg Rotor Angle: =60°
10	Adaptor	50 mlx4 4x2x1.5 ml 4x5 ml / 7 ml 4x10 ml 4x15 ml 4x20 ml



1



2



3



4



5



6



7



8



9



10



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com