



## -86°C ULT FREEZER BEZ-10801

# -86°C ULT FREEZER BEZ-10801

-86°C ULTRA-LOW FREEZER QUICKCOOL



Accurate temperature controller, setting temperature range of -40 to -86°C, and accuracy is 0.1 °C.

Suggested ambient temperature: +10 to 32°C.

Stainless steel inner chamber for friendly use and easy cleaning.

Brand compressor to ensure excellent stability of the cooling system.

Patented refrigeration technology, high-efficiency mixed gas for the cooling system.

Security

Safety door lock to prevent unauthorized access.

72h built-in backup battery to power the controller and save temp. data when power failure or system error.

Visual and audible alarm system: High/low temperature, sensor failure, controller

## SPECIFICATIONS

Model	BEZ-10801
Temperature Range	-40 ~ -86°C
Ambient Temperature	10~32°C
Capacity (L / Cu.Ft.)	60 / 2.12
Max Loading (2" Cryo-box / 2ml Cryo-vial)	24 / 2,400
Noise	50 dB
Controller / Display	Microprocessor / Digital
Sensor	PTC
Voltage & Frequency	220V±10%, 50/60Hz
Power	333 W
Electric Current	3.5 A
Power Consumption (kWh/24h)	5
High/Low Temp Alarm	Yes
Power Failure Alarm	Yes, 72h
Sensor Error Alarm	Yes
Controller Error Alarm	Yes
Door Ajar Alarm	Yes
Abnormal Voltage Alarm	Yes
Abnormal Ambient Temp Alarm	Yes
Battery Error Alarm	Yes
Condenser Error / Filter Net Clean Alarm	Yes
Refrigeration Type	Direct Cooling / Manual
Compressor (Brand/pcs)	CUBIGEL / 1
Refrigerant / Weight	R400A / 118g
Door (pcs)	Foamed Solid Door / 1
Inner Door (pcs)	Foamed Solid Door / 1
Adjustable Shelf (pcs)	1
Exterior / Interior Cabinet Material	Coated Steel / Stainless Steel
Insulation Material	PURF (≥120mm)
Door Lock	Yes
Test Hole (pcs)	1
Castors (pcs)	4
USB Data Download Port	Yes

Remote Alarm Port	Yes
RS485 Port	Optional
Temperature Datalogger	Optional
Temperature Printer	Optional
Protective Gloves	Optional
LN2/CO2 Backup System + LN2 Filling Tank	Optional
Interior Dimensions (WxDxH)	330x453x410 mm
Exterior Dimensions (WxDxH)	904x798x743 mm
Package Dimensions (WxDxH)	966x818x932 mm
Net / Gross Weight	94 / 128 kgs
Shipping Volume	0.74 CBM
Package	Plywood box with pallet
Alt Name	-86°C Ultra-low Freezer QuickCool



## FEATURES

Accurate temperature controller, setting temperature range of -40 to -86°C, and accuracy is 0.1 °C.

Suggested ambient temperature: +10 to 32°C.

Stainless steel inner chamber for friendly use and easy cleaning.

Brand compressor to ensure excellent stability of the cooling system.

Patented refrigeration technology, high-efficiency mixed gas for the cooling system.

### Security

Safety door lock to prevent unauthorized access.

72h built-in backup battery to power the controller and save temp. data when power failure or system error.

Visual and audible alarm system: High/low temperature, sensor failure, controller error, etc.

Power failure protection: turn-on delay of the cooling system after power failure.

Controller error protection: the cooling system will remember the normal working cycle and keep working depending on this memory when the controller or two sensors failed.

### Humanized design

Adjustable shelves for easy storage.

Special-designed service-free drainage system.

## APPLICATIONS

The -86°C ultra-low temperature freezers are designed for the long-term preservation of viruses, germs, vaccines, biological tissues and organs, special food, medicines, reagents, etc.



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)