



BLOOD BANK REFRIGERATOR BEZ1BF1 (BBBF-301)

BLOOD BANK REFRIGERATOR BEZ1BF1

4°C BLOOD BANK REFRIGERATOR



Microprocessor control, ensure the inside temperature of 4°C±1°C accuracy is 0.1°C
Suggested ambient temperature: +10~32°C.

Specially designed forced-air cooling system, ensures frost-free cabinet and good temperature uniformity.

Toughened glass door with heater to avoid condensation.

Wide available voltage range: 220V±10%.

Security

Safety door lock and controller password to prevent unauthorized access.

72h built-in backup battery to power the controller and save temp. data when power failure or system error.

Visual and audible alarm system.

SPECIFICATIONS

Model	BEZ1BF1
Old Model	BBBF-301
Temperature Range	4 ± 1°C
Ambient Temperature	10~32°C
Capacity (L / Cu. Ft.)	108 / 3.81
Interior Dimensions (WxDxH) mm	432x462x555
Exterior Dimensions (WxDxH) mm	522x635x1050
Weight	74 kgs
Noise	48 dB
Max Loading of 450/400/300/200ml Blood Bag	66/78/96/120 Bags
Controller	Microprocessor
Display	Digital
Sensor	NTC
Voltage and Frequency	220V±10%, 50/60Hz
Power	168 W
Electric Current	1.23 A
Power Consumption (kWh/24h)	2.1
High / Low Temp. Alarm	Yes
Power Failure Alarm	Yes, 72h
Sensor Error Alarm	Yes
Controller Error Alarm	Yes
Door Ajar Alarm	Yes
Battery Error Alarm	Yes
Refrigeration Type	Forced-air Cooling
Defrost	Auto
Compressor (Brand/pcs)	EMBRACO / 1
Refrigerant / Weight	R134a / 60g
Door (pcs)	Self-closing Foamed Heating Glass Door / 1
Inner Door (pcs)	PMMA / 2
Adjustable Shelf (pcs)	2
Basket (pcs)	6

Interior Cabinet Material	Stainless Steel
Exterior Cabinet Material	Coated Steel
Insulation Material	PURF (δ45mm)
Door Lock	Yes
LED Lamp	Yes
Test Hole (pcs)	1
Castors (pcs)	4
Remote Alarm Port	Yes
Temperature Printer	Yes
USB Data Download Port	Optional
RS485 Port	Optional
Temperature Datalogger	Optional
Package	Plywood box with pallet
Shipping Weight	95 kgs
Shipping Size (WxDxH) mm	700x590x1210
Shipping Volume	0.5 CBM
Alt Name	4°C Blood Bank Refrigerator



FEATURES

Microprocessor control, ensure the inside temperature of 4°C±1°C accuracy is 0.1°C

Suggested ambient temperature: +10~32°C.

Specially designed forced-air cooling system, ensures frost-free cabinet and good temperature uniformity.

Toughened glass door with heater to avoid condensation.

Wide available voltage range: 220V±10%.

Security

Safety door lock and controller password to prevent unauthorized access.

72h built-in backup battery to power the controller and save temp. data when power failure or system error.

Visual and audible alarm system.

Power failure protection: turn-on delay of the cooling system after power failure.

Controller error protection: the cooling system will remember the normal working cycle and keep working depending on this memory when the controller or two sensors failed.

Humanized design

Special designed service-free drainage system, ensure no water in the cabinet.

Adjustable shelves and blood baskets for easy storage.

Castors with stoppers for easy moving and fixation.

Auto on/off LED light with manual switch on the control panel.

Auto on/off cooling fan to prevent cold air from leaking out when the door is opening.

APPLICATIONS

Blood bank refrigerators are specially designed to store blood bags and blood-derived products.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com