



## -25Â°C FREEZER BEZ1K1 (BFUR-25-505)

# -25Â°C FREEZER BEZ1K1

-25Â°C BIOMEDICAL FREEZER



Microprocessor control, ensure good inner temperature uniformity, accuracy is 0.1Â°C

HC green refrigerant is energy-saving and environmentally friendly.

Wide available voltage range: 220VÂ±10%.

Security

Safety door lock and controller password to prevent unauthorized access.

Built-in backup battery to display temperature and alarms when power failure or system error.

Visual and audible alarm system.

Inner doors to prevent cold air from leaking out when the outside door is opening.

Power failure protection: turn-on delay of the cooling system after power failur

## SPECIFICATIONS

Model	BEZ1K1
Old Model	BFUR-25-505
Temperature Range	-10 ~ -25Â°C
Ambient Temperature	10~32Â°C
Capacity (L/Cu.Ft.)	936 / 33.1
Interior Dimensions (WxDxH) mm	1000x700x1335
Exterior Dimensions (WxDxH) mm	1304x1000x2017
Weight	378 kgs
Noise	50 dB
Controller	Microprocessor
Display	Digital
Sensor	PTC
Voltage and Frequency	220VÂ±10%, 50/60Hz
Power	1000 W
Electric Current	5.8 A
Power Consumption (kWh/24h)	10
High / Low Temp. Alarm	Yes
Power Failure Alarm	Yes, 72h
Sensor Error Alarm	Yes
Controller Error Alarm	Yes
Door Ajar Alarm	Yes
Abnormal Voltage Alarm	Yes
Abnormal Ambient Temp. Alarm	Yes
Battery Error Alarm	Yes
Condenser Error Alarm	Yes
Filter Net Clean Alarm	Yes
Refrigeration Type	Direct Cooling
Defrost	Manual
Compressor (Brand/pcs)	SECOP / 2
Refrigerant / Weight	R404A / 320g
Door (pcs)	Foamed Solid Door / 1

Inner Door (pcs)	Foamed Solid Door / 4
Adjustable Shelf (pcs)	3
Interior Cabinet Material	Stainless Steel
Exterior Cabinet Material	Coated Steel
Insulation Material	PURF (î120mm)
Door Lock	Yes
Test Hole (pcs)	1
Castors (pcs)	4
USB Data Download Port	Yes
Remote Alarm Port	Yes
RS485 Port	Optional
Temperature Datalogger	Optional
Temperature Printer	Optional
Temperature Chart Recorder	Optional
Package	Plywood box with pallet
Shipping Weight	413 kgs
Shipping Size (WxDxH)	1370x1110x2200
Shipping Volume	3.35 CBM
Alt Name	-25Â°C Biomedical Freezer



## FEATURES

Microprocessor control, ensure good inner temperature uniformity, accuracy is 0.1Â°C

HC green refrigerant is energy-saving and environmentally friendly.

Wide available voltage range: 220VÂ±10%.

### Security

Safety door lock and controller password to prevent unauthorized access.

Built-in backup battery to display temperature and alarms when power failure or system error.

Visual and audible alarm system.

Inner doors to prevent cold air from leaking out when the outside door is opening.

Power failure protection: turn-on delay of the cooling system after power failure.

Controller error protection: the cooling system will remember the normal working cycle and keep working depending on this memory when the controller or two sensors failed.

### Humanized design

Adjustable shelves for easy storage.

Casters with stoppers for easy moving and fixation.

## APPLICATIONS

The -25Â°C medical deep freezers are designed to store vaccines, blood plasma, reagents, and many other biological materials which are widely used in research institutions, clinics, and medical fields.



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada  
Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)