



-40Â°C FREEZER BEZ1T1 (BFRZ-40-401)

-40°C FREEZER BEZ1T1

-40°C CHEST BIOMEDICAL FREEZER



Accurate temperature controller, setting temperature range is -20 to -40°C, accuracy is 0.1 °C.

Suggested ambient temperature: +10 to 32°C.

Brand compressor to ensure excellent stability of the cooling system.

HC eco-friendly refrigerant and high-efficiency cooling system.

Security

Visual and audible alarm system: High/low temperature, sensor failure, controller error.

Power failure protection: turn-on delay of the cooling system after power failure.

Controller error protection: the cooling system will remember the normal working cycle and keep working depending on this memory when the controller or two sens

SPECIFICATIONS

Model	BEZ1T1
Old Model	BFRZ-40-401
Temperature Range	-20 ~ -40°C
Ambient Temperature	10~32°C
Capacity (L / Cu. Ft.)	105 / 3.71
Interior Dimensions (WxDxH) mm	480x380x665
Exterior Dimensions (WxDxH) mm	694x686x942
Weight	50 kgs
Noise	50 dB
Controller	Microprocessor
Display	Digital
Sensor	NTC
Voltage and Frequency	220V±10%, 50/60Hz
Power	175W
Electric Current	1.59 A
Power Consumption (kWh/24h)	1.49
High / Low Temp. Alarm	Yes
Power Failure Alarm	Yes, 12h
Sensor Error Alarm	Yes
Controller Error Alarm	Yes
Refrigeration Type	Direct Cooling
Defrost	Manual
Compressor (Brand/pcs)	CUBIGEL / 1
Refrigerant / Weight	R290 / 40g
Door (pcs)	Foamed Solid Door / 1
Interior Cabinet Material	Coated Steel
Exterior Cabinet Material	Coated Steel
Insulation Material	PURF (î100mm)
Door Lock	Yes
Test Hole (pcs)	1
Castors (pcs)	4

Temperature Datalogger	Optional
Basket (pcs)	Optional
Package	Carton box with pallet
Shipping Weight	70 kgs
Shipping Size (WxDxH) mm	770x705x1090
Shipping Volume	0.59 CBM
Alt Name	-40Â°C Chest Biomedical Freezer



FEATURES

Accurate temperature controller, setting temperature range is -20 to -40Â°C, accuracy is 0.1 Â°C.

Suggested ambient temperature: +10 to 32Â°C.

Brand compressor to ensure excellent stability of the cooling system.

HC eco-friendly refrigerant and high-efficiency cooling system.

Security

Visual and audible alarm system: High/low temperature, sensor failure, controller error.

Power failure protection: turn-on delay of the cooling system after power failure.

Controller error protection: the cooling system will remember the normal working cycle and keep working depending on this memory when the controller or two sensors failed.

Humanized design

Casters with stoppers for easy moving and fixation.

Special-designed service-free drainage system.



Datalogger

APPLICATIONS

The -40 Â°C medical deep freezers are designed to store vaccines, blood plasma, reagents, and many other biological materials which are widely used in research institutions, clinics, and medical fields.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com