



## -86Â°C ULT FREEZER BEZ2B1

# -86Â°C ULT FREEZER BEZ2B1

-86Â°C ULTRA-LOW FREEZER SAFECOOL



Two separate cooling systems in one freezer, if one of them fails, the backup cooling system will start to work automatically.  
Security and Reliable, advanced technology, standard backup system, one system can keep the freezer inside temperature at -70Â°C.  
Accurate temperature controller, setting temperature range of -40 to -86Â°C  
7-inch touch screen display, accuracy of 0.1 Â°C.  
Suggested ambient temperature: +10 to 32Â°C.  
Stainless steel inner chamber for friendly use and easy cleaning.  
Brand compressor to ensure excellent stability of the cooling system.  
Security  
Safety door lock to prevent unauthorized access.  
72h built-in backup battery to power the controller and save temp. data when pow

## SPECIFICATIONS

Model	BEZ2B1
Temperature Range	-40 ~ -86Â°C
Ambient Temperature	10~32Â°C
Capacity (L / Cu.Ft.)	728 / 25.71
Noise	55 dB
Cold Rack Max Loading (pcs)	25D Rack / 18, 24D Rack / 6
2" Cold Box Max Loading (pcs)	504
0.5/2ml Vials Max Loading (pcs)	50,400
Controller / Display	Microprocessor / 7" Touch Screen
Sensor	PTC
Voltage & Frequency	220VÂ±10%, 50Hz
Power	1400 W
Electric Current	10.37 A
Power Consumption (kWh/24h)	23.44
High/Low Temp Alarm	Yes
Power Failure Alarm	Yes, 72h
Sensor Error Alarm	Yes
Controller Error Alarm	Yes
Door Ajar Alarm	Yes
Abnormal Voltage Alarm	Yes
Abnormal Ambient Temp Alarm	Yes
Battery Error Alarm	Yes
Condenser Error / Filter Clean Alarm	Yes
Refrigeration Type	Direct Cooling / Manual
Compressor (Brand/pcs)	SECOP / 2
Refrigerant / Weight	R400A / 370g
External / Internal Door	Foamed Solid Door x 1 / Foamed Solid Door x 2
Adjustable Shelf (pcs)	3
Exterior / Interior Cabinet	Coated Steel / Stainless Steel
Insulation Material	PURF (â‰¥100mm) + VIP
Test Hole (pcs)	2

Door Lock	Yes
Castors (pcs)	4
USB Data Download Port	Yes
Remote Alarm Port	Yes
RS485 Port	Yes
Temperature Datalogger	Optional
Temperature Printer	Optional
Temperature Chart Recorder	Optional
Protective Gloves	Optional
LN2/CO2 Backup System	Optional
Interior Dimensions (WxDxH)	963x571x1350 mm
Exterior Dimensions (WxDxH)	1248x975x1995 mm
Packing Dimensions (WxDxH)	1330x1020x2200 mm
Net / Gross Weight	316 / 392 kgs
Package	Plywood box with pallet
Alt Name	-86Â°C Ultra-low Freezer SafeCool



## FEATURES

Two separate cooling systems in one freezer, if one of them fails, the backup cooling system will start to work automatically.  
 Security and Reliable, advanced technology, standard backup system, one system can keep the freezer inside temperature at -70Â°C.  
 Accurate temperature controller, setting temperature range of -40 to -86Â°C  
 7-inch touch screen display, accuracy of 0.1 Â°C.  
 Suggested ambient temperature: +10 to 32Â°C.  
 Stainless steel inner chamber for friendly use and easy cleaning.  
 Brand compressor to ensure excellent stability of the cooling system.

### Security

Safety door lock to prevent unauthorized access.  
 72h built-in backup battery to power the controller and save temp. data when power failure or system error.  
 Visual and audible alarm system: High/low temperature, sensor failure, controller error, etc.  
 Power failure protection: turn-on delay of the cooling system after power failure.  
 Controller error protection: the cooling system will remember the normal working cycle and keep working depending on this memory when the controller or two sensors failed.

### Humanized design

Adjustable shelves for easy storage.  
 Casters with stoppers for easy moving and fixation.  
 Special-designed service-free drainage system.

## APPLICATIONS

The -86Â°C ultra-low temperature freezers are designed for the long-term preservation of viruses, germs, vaccines, biological tissues and organs, special food, medicines, reagents, etc.



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada  
Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)