



## MINI-PCR BFA1P2 (BHTC-502)

## MINI-PCR BFA1P2

### MINI GRADIENT THERMAL CYCLER

Mini Thermal Cycler is an ultra-light and ultra-thin thermal cycle gene amplification instrument. Widely used in molecular biology, criminal investigation, disease research and other fields. Mini portable for car use.



New and unique appearance, the interface operation is simple and convenient, ultra-light ultra-thin.

Hot lid can be switched on and off, and test tube temperature control mode and module temperature control mode can be choose to meet more different experimental requirements.

The mini PCR can be used in vehicles

Can be quickly upgraded via U disk, convenient for instrument software update.

#### A. Details

The latest generation of semiconductor technology, excellent augmentation performance, effectively eliminate the edge effect of module heat conduction, the module temperature uniformity is excellent. Built-in multiple refrigeration film, multiple sensors are evenly distributed, the program temperature control is more p

## SPECIFICATIONS

Model	BFA1P2
Old Model	BHTC-502
Single step time range	1~59m59s (0 is forever)
Temp. range	4~99.9°C
Sample capacity	16x0.2ml
Max. heating rate	5°C/s
Max. cooling rate	4°C/s
Temp. uniformity	±0.25°C
Temp. accuracy	±0.20°C
Temp. display resolution	0.1°C
Temp. control method	Block/Tube
Gradient temp. uniformity	/
Gradient temp. accuracy	/
Gradient temp. range	/
Gradient temp. difference range	/
Hot cover temp. range	30~110°C
Max. steps of the program	30
Program max. cycle number	99
Time increment/decrement	-599~+599s
Temp. increase/decrease	-9.9~+9.9°C
Program pause function	Yes
16°C Insulation	Forever
LCD	5 inch, 800x480 Pixel
Program storage quantity	>100
Communication Interface	USB 2.0
Input power	12V 9.99A
Dimensions	W.200xD.230xH.85mm
Net weight	3.2kg
Alt Name	Mini Gradient Thermal Cycler

## FEATURES

New and unique appearance, the interface operation is simple and convenient, ultra-light ultra-thin.

Hot lid can be switched on and off, and test tube temperature control mode and module temperature control mode can be choose to meet more different experimental requirements.

The mini PCR can be used in vehicles

Can be quickly upgraded via U disk, convenient for instrument software update.

### A. Details



The latest generation of semiconductor technology, excellent augmentation performance, effectively eliminate the edge effect of module heat conduction, the module temperature uniformity is excellent. Built-in multiple refrigeration film, multiple sensors are evenly distributed, the program temperature control is more precise.



The bottom case is made of one-piece aluminum, which is not only beautiful and sturdy, but also has a higher heat dissipation performance.



The ingenious elastic hot-cover structure design adapts the test tubes of different heights to ensure the best conditions for the experiment.



5-inch TFT high-definition full-touch color screen, can quickly edit the required files, visual display of temperature curve, convenient and fast setting.

### B. Software function introduction



Gradient interface(MP-32+) System built-in gradient



Running interface(MP-32+)

Real-time display of gradient distribution and real-time temperature display.



Setting interface

Hot lid temperature and working mode of hot lid can be set.



User interface (more than 100 files can be stored)

Multi-user independent detection and independent management.



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)