





# FLOOR TYPE FREEZE DRYER BFB1G2 (BFFT-101-B)





# FLOOR TYPE FREEZE DRYER BFB1G2

#### FREEZE DRYER

Compact, stainless steel unit with casters for easy movement, Floor type freeze dryer provides unmatched process accuracy and reliability in performance. It optimizes your space requirements and reduces energy consumption.



Condenser, operation panel, shelves and trays are made of stainless steel Drying chamber is equipped with organic glass for safety and visibility Low noise compressor with long shelf life and high efficiency Features vacuum freeze drying technology Drying curves are displayed on LCD screen Condenser has pre-freezing function CFC free environment friendly refrigeration with low maintenance Features nitrogen valve and eutectic test device (optional)

#### **SPECIFICATIONS**

Model	BFB1G2		
Old Model	BFFT-101-B		
Capacity	1.2 L		
Condenser Temperature	-80°C		
Water Holding Capacity	3-4 /24h		
Freeze Drying Surface Area	0.12 m²		
Pre Freeze Shelf Dimension	φ 200 mm		
Vacuum Degree	< 10 Pa		
Pump Flow Rate	2 L/sec		
Overall Dimension (mm)	660 x 460 x (710 + 430)		
Shelves	4		
Weight	110 kg		
Power	1070		
Power Supply	220V, 50Hz		
Alt Name	Standard Type		

#### **ACCESSORIES FOR PURCHASE**

No	Name	Description	Trays	Temperature
1	Nitrogen inflation valve			
2	Exhaust filter/ Oil mist filter for pump			
3	Air inlet filter for pump			
4	Anti oil return valve for pump			
5	Electricity heating defrosting			
6	Electric heating shelf			
7	Trays	Trays: dia. 180mm / dia. 200mm	Diameter 180mm / 200mm	
8	RS232 and software	Check and keep freeze drying data on computer; control freeze dryer through PC		

9 -80°C Condenser Minimum condenser temperature as -80°C Min. condenser temperature as -80°C

### **APPLICATIONS**

Perishable Substances, Waste Products, Laboratory, Research, Proteins, Organic Tissues, Waste Products, Plant Material, Polymers, Pharmaceuticals, Nutraceuticals, Plant material.



# Biolab Scientific Ltd.