


FLOOR TYPE FREEZE DRYER BFB1K2 (BFFT-105-B)

FLOOR TYPE FREEZE DRYER BFB1K2

FREEZE DRYER

Compact, stainless steel unit with casters for easy movement, Floor type freeze dryer provides unmatched process accuracy and reliability in performance. It optimizes your space requirements and reduces energy consumption.



Condenser, operation panel, shelves and trays are made of stainless steel
Drying chamber is equipped with organic glass for safety and visibility
Low noise compressor with long shelf life and high efficiency
Features vacuum freeze drying technology
Drying curves are displayed on LCD screen
Condenser has pre-freezing function
CFC free environment friendly refrigeration with low maintenance
Features nitrogen valve and eutectic test device (optional).

SPECIFICATIONS

Model	BFB1K2
Old Model	BFFT-105-B
Condenser Temperature	-80°C
Water Holding Capacity	3-4 /24h
Vacuum Degree	< 10 Pa
No of Sealed Valves	24 pieces for 24 ampoules
Overall Dimension (mm)	660x460x(710+430)
Weight	80/110 kg
Power	1070
Power Supply	220V, 50Hz
Alt Name	T-Floor type

ACCESSORIES FOR PURCHASE

No	Name	Description	Trays	Temperature
1	Nitrogen inflation valve			
2	Exhaust filter/ Oil mist filter for pump			
3	Air inlet filter for pump			
4	Anti oil return valve for pump			
5	Electricity heating defrosting			
6	Electric heating shelf			
7	Trays	Trays : dia. 180mm/ dia.200mm	Diameter 180mm/200mm	
8	RS232 and software	Check and keep freeze drying data on computer; control freeze dryer through PC		
9	-80°C Condenser	Minimum condenser temperature as -80°C		Min. condenser temperature as -80°C

APPLICATIONS

Perishable Substances, Waste Products, Laboratory, Research, Proteins, Organic Tissues, Waste Products, Plant Material, Polymers, Pharmaceuticals, Nutraceuticals, Plant material.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com