



LABORATORY LOW SPEED CENTRIFUGE BFH-1901

LABORATORY LOW SPEED CENTRIFUGE BFH-1901

PRP CENTRIFUGE



1. Maintenance -free brushless motor
2. LCD display of Speed, RCF and time.
3. Adjustable speed from 300r/min to 5000r/min
4. Timer from 1s to 99min or continuous operation
5. Lid automatically open at the end of run to prevent sample warming and to reduce handling time.
6. 10 Program stored in memory and editable by ender user.
7. 10 Acceleration/ 10 Deceleration profiles ,with soft brake system to get the good separation effect.
8. Electric cover lock, compact design, super speed and imbalance protection.

SPECIFICATIONS

Model	BFH-1901
Max. Speed	5000rpm
Max. RCF	2635xg
Max. Capacity	6x10ml/15ml PRP tube, 4x30ml PRP tube with adapters for 15ml/20ml prp tubes
Time Range	0~99min
RPM/RCF Convert	Yes
Noise (dB)	≤ 55
Acc/Dec	10 levels
Speed Accuracy	± 20r/min
Voltage(V/Hz)	AC 220V/110V 50HZ/60HZ
Size (W x D x Hmm)	280x220x175mm
Net Weight(Kg)	3.5 KG
Certificates	CE, ISO & Calibration report are available
Alt Name	PRP Centrifuge



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com