



LABORATORY LOW SPEED CENTRIFUGE BFH-5301

LABORATORY LOW SPEED CENTRIFUGE BFH-5301

GERBER CENTRIFUGE



1. Microprocessor control, digital display, touch panel, parameters in running can be edited and change to display other running parameter and RCF.
2. Brushless frequency motor with simpler construction, more reliable performance, longer life and quietly running.
3. Automatic lid lock, super speed, over temperature protection and imbalance protection.
The centrifuge body is made of high quality steel, safe and reliable.
4. Adapters are available by experiment requirements.
5. 3 tiers protection steel cover, safe and reliable.
6. TUV CE EMC certificate.

SPECIFICATIONS

Model	BFH-5301
Max. Speed	2000rpm
Max. RCF	750xg
Max. Capacity	8 tubes
Time Range	0~99min59sec
RPM/RCF Convert	Yes
Noise	≤ 58dBA
Speed Accuracy	±20rpm
Acc/Dec	10 Kinds
Temperature accuracy	/
Temperature range	Normal
Power supply	AC 220V/110V 50HZ/60HZ
Size (W x D x Hmm)	570x400x320mm
Net Weight(Kg)	40KG
Certificates	CE,ISO & Calibration report are available
Alt Name	Gerber Centrifuge



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com