



LABORATORY LOW SPEED CENTRIFUGE BFH1BR1 (BCBL-402)

LABORATORY LOW SPEED CENTRIFUGE BFH1BR1

PORTABLE LOW SPEED CENTRIFUGE



1. Maintenance -free brushless motor
2. LCD display of Speed, RCF and time.
3. Adjustable speed from 300r/min to 5000r/min
4. Timer from 1s to 99min or continuous operation
5. For 6x15ml centrifuge tube & 10ml/7ml/5ml/3ml blood collection tube or 4x50ml centrifuge tube.
6. Lid automatically open at the end of run to prevent sample warming and to reduce handling time.
7. 10 Program stored in memory and editable by ender user.
8. 10 Acceleration/ 10 Deceleration profiles ,with soft brake system to get the good separation effect.
9. Electric cover lock, compact design, super speed and imbalance protection.

SPECIFICATIONS

Model	BFH1BR1
Old Model	BCBL-402
Max. Speed	5000rpm
Max. RCF	2635xg
Max. Volume	4x50ml
Time Range	0~99min59sec
RPM/RCF Convert	Yes
Noise	≤ 55dBA
Temperature	Normal
Acc/Dec	10 Kinds
Speed Accuracy	±20rpm
Size (W x D x Hmm)	280x220x175mm
Net Weight(Kg)	3.5KG
Power supply	AC 220V/110V 50HZ/60HZ
Certificates	CE,ISO & Calibration report are available
Alt Name	Portable Low Speed Centrifuge

ITEMS INCLUDED

No	Rotor No. (Any one rotor)	Name	Max Speed (rpm)	Max Volume (ml)	Max RCF (g)
1	31501	Angle Rotor	5000	4x50ml	2615
2	31502	Angle Rotor	5000	6x15/10ml	2635
3	31502	Angle Rotor	5000	6x7ml vacuum tube adapter	2635
4	31502	Angle Rotor	5000	6x5ml vacuum tube adapter	2635

APPLICATIONS

Widely used in clinical or research lab.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com