



DOUBLE BEAM UV VISIBLE SPECTROPHOTOMETER BFJ1B4

DOUBLE BEAM UV VISIBLE SPECTROPHOTOMETER BFJ1B4

MICRO-SPECTROPHOTOMETERS



1. 7-inch capacitive TFT screen, multi-touch, intuitive interface, simple operation.
2. It has its own automatic detection function, which significantly improves the detection Efficiency.
3. With high-precision motor drive, the accuracy of the optical path reaches 0.001mm, and the absorbance detection repeatability is high.
4. The sample volume required for the test is only 0.5 to 2ul, and it can be recovered after the measurement.
5. It has dual-channel fluorescence detection function, high sensitivity and good linearity.
6. OD600 function with stirring and heating function can detect the growth of ba


SPECIFICATIONS

Model	BFJ1B4
Volume	0.5ul-2ul
Dimension	318x210x188mm (LxWxH)
Weight	4.5kg
Optical Path	0.03mm, 0.05mm, 0.1mm, 0.2mm, 1mm
Light Source	Xenon flash lamp/number of flashes
Detector Type	2048 pixel linear array CCD
Wavelength Range	190nm-850nm
Accuracy	±1nm
Spectral Resolution	≤3nm (FWHM@Hg253.7nm)
Absorption Accuracy	0.002Abs (1mm optical path)
Absorption Accuracy (260nm)	±1%(7.332Abs absorbance @ 260nm)
Absorbance Range	0.04-750(at 260nm wavelength, equivalent to 10mm optical path)
Concentration Range	2ng/ul dsDNA-37500ng/ul dsDNA
Detection Time	<6s
OD600 Light Source	/
OD600 Absorbance Range	/
OD600 Absorbance Stability	/
OD600 Repeatability	/
OD600 Absorption Accuracy	/
Heating Temperature	/
Stirring Speed	/
Fluorescence Sample Volume	/
Fluorescence Detection Time	/
Detection Channel	/
Reproducibility	/
Stability	/
Linearity	/
Light Source (Fluorescence)	/
Excitation Wavelength	/
Emission Wavelength	/
Printing	Built-in thermal printer
Communication	USB2.0 x2

Data Export Formats	xls, csv, txt, jpg, png
Experimental Data	>10,000
Input Voltage	DC12V 5A
Power Supply	60W
Alt Name	Micro-Spectrophotometers

FEATURES

1. 7-inch capacitive TFT screen, multi-touch, intuitive interface, simple operation.
2. It has its own automatic detection function, which significantly improves the detection Efficiency.
3. With high-precision motor drive, the accuracy of the optical path reaches 0.001mm, and the absorbance detection repeatability is high.
4. The sample volume required for the test is only 0.5 to 2ul, and it can be recovered after the measurement.
5. It has dual-channel fluorescence detection function, high sensitivity and good linearity.
6. OD600 function with stirring and heating function can detect the growth of bacteria, microorganisms, etc



Adopting Android operating system, 7-inch capacitive touch screen, no need for computer online, stand-alone can be detected



Rapid and accurate detection of nucleic acids, proteins and cellular solutions with only 0.5-2ul of sample.



Equipped with OD600 optical path detection system, fluorometer function, convenient for bacteria, microorganisms and other culture solution concentration detection.

APPLICATIONS

Rapid testing
Easy operation



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com