





THERMAL CYCLER BFN1D2





THERMAL CYCLER BFN1D2

THERMAL CYCLER



10.1" color TFT capacitive touch screen, beautiful interface and smooth operation Direct-acting pull-type electromagnet control, open the lid with one click Reserved mechanical lid opening function, open the heat lid safely in case of an accident

Run 3 PCR tests independently at the same time, avoid waiting for a long time Set variable temperature rates for each section, to meet demanding experimental requirements

8G internal storage, equipped USB interface for storage extension and data import or export

Replace the sample holders easily and quickly without tools, convenient maintenance

SPECIFICATIONS

Model	BFN1D2
Туре	Performance edition
Sample holder replacement	Support
Independent operation of sample holders	Support
Electromagnetic control lock	Support
Sample holder specifications	32 wells*0.2ml*3
Screen	10.1" color touch screen
Maximum heating rate	≥8 °C/s
Maximum cooling rate	≥5 °C/s
Average heating rate	≥3.5 °C/s (55 °C - 95 °C)
Average cooling rate	≥2.3 °C/s (95 °C - 55 °C)
Temperature uniformity	±0.15 °C (95 °C constant for 10s)
Temperature accuracy	≤0.1 °C
Temperature increasing/decreasing	0.1 - 10.0 ℃
Time increasing/decreasing	Standard
Single module gradient function	Support
Power failure protection	Support
Storage capacity	8G (USB expandable)
Maximum number of cycles	999
Communication interface	USB 2.0, LAN
Operating system	Android
Dimension (L*W*H mm)	502*394*293
Net weight (kg)	18
Alt Name	Thermal Cycler

FEATURES



10.1" color TFT capacitive touch screen, beautiful interface and smooth operation



Direct-acting pull-type electromagnet control, open the lid with one click Reserved mechanical lid opening function, open the heat lid safely in case of an accident



Run 3 PCR tests independently at the same time, avoid waiting for a long time Set variable temperature rates for each section, to meet demanding experimental requirements



8G internal storage, equipped USB interface for storage extension and data import or export Replace the sample holders easily and quickly without tools, convenient maintenance



Biolab Scientific Ltd.