



## CO2 INCUBATOR AIR JACKETED BFN1G1 (BCAJ-301)

# CO2 INCUBATOR AIR JACKETED BFN1G1

## CO2 INCUBATOR

CO2 incubators are widely used in scientific research to grow and maintain cell cultures. A Heal Force CO2 incubator provides you with unsurpassed natural simulation to ensure optimum growth conditions for your culture at all time. That's why they become the first choice of researchers in fields of application include tissue engineering, in vitro fertilization, neuroscience, cancer research and other mammalian cell research.



Safe for cultivation Cancer research

Cell cultivation in particular is a highly sensitive process in which bacteria, viruses, fungal spores and mycoplasmas can destroy valuable cultures or distort test results, causing more work. Heal Force solves this problem using a unique design and effective method to ensure sterile conditions.



Easy-to-clean design:

The cleaning process is significantly simplified by Heal Force's unique, seamless, deep-drawn interior chamber, which reduces any areas where contamination could accumulate. Heal Force incubators offer the best usable-space-to-volume ratio due to the total absence of any additional fittings in the interior chamber.

Coved comers

Inlet filter for CO2 supply:

All gas injection lines are filtered via HEPA filter to remove impurities and contaminants before being injected into the chamber. The HEPA filter is able to filter particles larger than 0.3um at 99.998%.

CO2 Inlet filter

Absolutely condensation-free, even at high air humidity level:

## SPECIFICATIONS

Model	BFN1G1
Old Model	BCAJ-301
Construction	
--Exterior dimensions (WxDxH, mm/inch)	637x762x909 (25.1x30x35.8)
--Interior dimensions (WxDxH, mm/inch)	470x530x607 (18.5x20.8x23.9)
--Interior Volume (L/cu.ft)	151L/5.3 cu.ft.
--Net Weight	80kg/176lbs
--Interior Material	Type 304, mirror finish, stainless steel
--Exterior Material	Electrolyzed galvanization steel, powder coated
--Inner door	3 inner doors standard
Temperature	
--Heating method	Direct Heat & Air Jacket (DHA)
--Temp. control system	Microprocessor
--Temp. sensor	PT1000
--Temp. range	5°C above ambient temperature to 50°C
--Temp. uniformity	±0.2°C
--Temp. stability	±0.1°C
CO2	
--Inlet pressure	0.1 MPa

--CO <sub>2</sub> control system	Microprocessor
--CO <sub>2</sub> sensor	Thermal conductivity
--CO <sub>2</sub> range	0 to 20%
--CO <sub>2</sub> stability	±0.1%
Humidity	
--Humidifying system	Special designed water reservoir
--Relative humidity	≥95%
--Water reservoir volume	3L
Shelves	
--Shelf dimensions (WxD, mm/inch)	423x445 (16.7x17.5)
--Shelf construction	Type 304, mirror finish, stainless steel
--Standard/Maximum shelves	3, 10
Fittings	
--Access port	Standard
--Air filter	0.3µm, Efficiency:99.998% (for CO <sub>2</sub> )
--Remote alarm contacts	Standard
De-contamination	90°C moist heat disinfection
Rated power	600W
Power supply	220V/50Hz (standard), 110V/60Hz (optional)
Alarm system	Power interruption * High/Low temperature * Deviation of CO <sub>2</sub> * RH * Door ajar * Independent overheat protection
Data output	RS232
Alt Name	CO <sub>2</sub> Incubator

## FEATURES

Easy-to-clean design:

The cleaning process is significantly simplified by Heal Force's unique, seamless, deep-drawn interior chamber, which reduces any areas where contamination could accumulate. Heal Force incubators offer the best usable-space-to-volume ratio due to the total absence of any additional fittings in the interior chamber.



Coved comers

Inlet filter for CO<sub>2</sub> supply:

All gas injection lines are filtered via HEPA filter to remove impurities and contaminants before being injected into the chamber. The HEPA filter is able to filter particles larger than 0.3µm at 99.998%.



CO<sub>2</sub> Inlet filter

Absolutely condensation-free, even at high air humidity level:

The high air humidity prevents cell cultures from drying out and also keeps the osmolarity constant in the culture medium. With our CO<sub>2</sub> incubators, you can work with air humidity up to 95% while the internal walls remain completely dry ( In order to prevent contamination, however, no condensation must occur). The patented tilted water reservoir system keeps the air humidity absolutely stable.



Water reservoir

#### Optimum temperature control:

A reliable air jacketed heating system combined with PT1000 temperature sensors ensures high precision with homogenous heat distribution in the interior.

Outstanding dynamics ensure short recovery times and balance out any fluctuations caused by door open for CO<sub>2</sub> incubators. This provide reliable protection at any time, particularly for sensitive cultures.

Note: The main heater provides precise temperature control.

The bottom heater warms the distilled water and ensures chamber humidity.

The outer door heater prevents condensation on the inner door and facilitates quick temperature recovery after door openings.



#### Divided, inner glass door:


Three inner glass doors maintains stable climatic conditions, minimizes any changes to the humidity, heat and gas concentration, shortens recovery times significantly and also further reduces the risk of contamination.



with 3 inner glass doors (standard)

#### 90°C moist heat disinfection:

They are equipped with 90 C moist heat disinfection system. The validated overnight sterilization cycle ensures reliable destruction of germs that could interfere with your work and requires no extra work, such as removal of interior fittings. Mycoplasma is 100% eliminated in a routine disinfection cycle.



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)