



LABORATORY LOW SPEED CENTRIFUGE BFS1BT1 (BCBLS-108)

LABORATORY LOW SPEED CENTRIFUGE BFS1BT1

SPINPLUS CENTRIFUGE

The Spinplus is the most powerful and competitive centrifuge.

placed 6-8 of 20 ml glass tube or 15 ml conical centrifuge tube.

400-5000 rpm/min, the RPI / RCF indicated in LCD display can be switched. This centrifuge is ideal for the separation of serum, plasma, urea, blood samples and other routine applications in hospital and research laboratories.



Gentle deceleration for efficient sample separation.

Automatic lid opening system saves operating time.

The LCD display indicated time/speed for clear and easy operation.

Available for Shortspin operation mode, timed operation mode, improve efficiency.

Safety lid-lock prevent opening the centrifuge lid until the rotor has stopped spinning.

Operation timer range from 10 seconds to 99 minutes, with bell signal after finish operation.

The acceleration and deceleration can be controlled between 20-80 seconds at speed of 0-5000 RPM.

Safety lid-lock

SPECIFICATIONS

Model	BFS1BT1
Old Model	BCBLS-108
Power supply	110V-60Hz or 230V-50/60Hz
Power requirement	40W
Max. speed	400-5000 rpm (in 100 rpm increments)
Relative centrifugal force (rcf)	3074 xg
Timer	15 sec ~ 99 min
Acceleration time to max. speed	20-80 seconds available
Braking time from max. speed	20-80 seconds available
Alt Name	Spinplus Centrifuge

FEATURES

Gentle deceleration for efficient sample separation.

Automatic lid opening system saves operating time.

The LCD display indicated time/speed for clear and easy operation.

Available for Shortspin operation mode, timed operation mode, improve efficiency.

Safety lid-lock prevent opening the centrifuge lid until the rotor has stopped spinning.

Operation timer range from 10 seconds to 99 minutes, with bell signal after finish operation.

The acceleration and deceleration can be controlled between 20-80 seconds at speed of 0-5000 RPM.

Safety lid-lock

LCD display showing

Open lid automatically

The operation interface simple and easy

RPM and RCF can be switched in display showing

6/8 of 15 ml conical centrifuge tubes with screw caps can be placed



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com