



PIPETTE CONTROLLER BFS1W2

PIPETTE CONTROLLER BFS1W2

MOTORIZE PIPETTE CONTROLLER

Motorize pipette controllers are light weight only 170 g and designed to fit comfortably in either the right or left hand. The natural feel of the ergonomic body design, the computer-balanced weight distribution, and the low-pressure fingertip control buttons all combine to provide a more comfortable pipetting experience. Set your instruments down on the bench without risking contamination using the proprietary quickstand.



Operating

Comfortable:

Ergonomic handgrip, weight only 190 g, perfectly balanced design - for fatigue-free pipetting even in prolonged operations.

Single-Handed Operation:

With a pipette controller, you have continuously variable speed control using just two buttons. In addition, you can select your preferred maximum motor speed to improve sensitivity and control with low-volume pipettes.

Powerful and Quiet:

At maximum motor speed, a 50 ml pipette is filled in less than 10 seconds. Now that's fast! The motor and pump operate quietly and with very low vibration. The longer you use it, the more you will appreciate it.

SPECIFICATIONS

Model	BFS1W2
Colour	Magenta
Weight	190
Operating and charging temperature	+10°C to 35°C
Pipetting Speed	50ml in less than 10 seconds
For glass and plastic pipettes	0.1 to 200ml
Pipetting Time	Approx. twelve hours of continuous, pipetting(with a 10ml pipette)
Without recharging battery pack	Lithium battery 2.4V/700mah
MOQ-20PCS	
Alt Name	Motorize Pipette Controller

FEATURES

Operating

Comfortable:

Ergonomic handgrip, weight only 190 g, perfectly balanced design - for fatigue-free pipetting even in prolonged operations.

Single-Handed Operation:

With a pipette controller, you have continuously variable speed control using just two buttons. In addition, you can select your preferred maximum motor speed to improve sensitivity and control with low-volume pipettes.

Powerful and Quiet:

At maximum motor speed, a 50 ml pipette is filled in less than 10 seconds. Now that's fast! The motor and pump operate quietly and with very low vibration. The longer you use it, the more you will appreciate it.


Advanced Charging:

The intelligent battery charger prevents overcharging of the NiMH battery. It effectively reduces the lazy-battery effect (shortened operating time due to premature recharging). No need to worry about having enough battery power left to finish your series. A flashing LED light will alert you approx. two hours in advance.



Direct exhaust of liquid vapors protects against corrosion to ensure long instrument life.

Pipettes from 0.1 to 200 ml. The safety valve and 0.2 μm hydrophobic membrane filter provide double protection against fluid penetration.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com