



MOISTURE ANALYZER BFT-501

MOISTURE ANALYZER BFT-501

HALOGEN MOISTURE ANALYZER



Halogen lamp / HBM sensor
Aluminum shell / Stainless steel chamber
LCD (White back light with black font)
Temperature / Time set
The percentage of moisture content / Dry residual
Store historical set
Option: Aluminum box / Printer / Grinder / USB

SPECIFICATIONS

Model	BFT-501
Capacity	110g
Readability	0.01g
Operating Temp	5°C-35°C
Display	Backlit LCD
Calibration	External calibration
Interface	RS232(Standard) USB(Optional)
Pan Size	Φ90mm
Packing Size	485*340*350mm
Gross Weight	6.8kg
Heating Unit	Halogen lamp-1
Temp. Sensor	PT100
Temp. Range	40°C-199°C
Temp. Step	1°C
Moisture Range	0.0%-100.0%
Moisture Readability	0.2%
Dry Range	100.00%-0.00%
Dry Readability	0.2%
Temp Setting	40°C-199°C By 1°C Step
Time Setting	1-99min By 10s
Number Of Storage	15
Heater power	220V ±15% 50Hz / 110V ±15% 60Hz / 400W
Balance power	Input:220V 50Hz / 110V 60Hz Output:9V
Chamber Height	22mm
Alt Name	Halogen Moisture Analyzer

ACCESSORIES FOR PURCHASE

No	Name	Size	Material	Mat
1	Aluminum sample tray 1	Outer circle Φ 90mm Inner circle Φ 83mm Plate height 4mm	Aluminum	50 pieces/box
2	Portable aluminum box	48*44*24cm		

3	Temperature kit		
---	-----------------	--	--



1



2



3

FEATURES

Halogen lamp / HBM sensor

Aluminum shell / Stainless steel chamber

LCD (White back light with black font)

Temperature / Time set

The percentage of moisture content / Dry residual

Store historical set

Option: Aluminum box / Printer / Grinder / USB



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com