



ANALYTICAL BALANCE BFT1L5

ANALYTICAL BALANCE BFT1L5

INTERNAL CALIBRATION ANALYTICAL BALANCE



Internal calibration
 LCD (White back light with black font)
 One key / Time trigger internal calibration
 Electromagnetic force sensor
 Glass draft shield with 3 sliding doors for easy access to the items being weighed
 Tare function / Counting / Percentage
 Unit conversion (g/mg/ct/oz...)
 Sensitivity / Speed set
 Overload alarm / Fault alarm / Level indicator

SPECIFICATIONS

Model	BFT1L5
Capacity	1100g
Readability	0.1mg
Min weighing	0.4mg
Stable Time	≤4s
Display	LCD(white back light with black font)
Pan size	Φ80mm
Operation temp	5-35°C
Repeat ability	0.35mg from 310g to 610g
Linearity	± 0.5mg
Draft shield size	162mmx171mmx225mm
Cal.weight	Internal calibration
Interface	RS485/Printer(Optional)
Dimension	345x215x345mm
N. weight	7 kg
Alt Name	Internal Calibration Analytical Balance

ACCESSORIES FOR PURCHASE

No	Name	Description	Information
1	Weight set	Recommend corresponding accuracy calibration (1mg-20kg)	M1 level Suitable for 0.1g-0.01g



1



1



1



1



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com