



PRECISION BALANCE BFT1R3

PRECISION BALANCE BFT1R3

PRECISION BALANCE



Internal auto calibration / Strain gauge sensor
 LCD (White back light with black font)
 Tare function / Counting / Unit conversion
 Percentage / Sensitivity / Speed set
 Density / Peak holding
 Print function (Baud rate setting, Continuous communication or press communication)
 Calibration time setting
 Overload alarm / Fault alarm / Level indicator
 Option: USB / Printer / Density kit

SPECIFICATIONS

Model	BFT1R3
Capacity	220g
Readability	0.001g
Min weighing	0.004g
Repeatability	±0.002g
Linearity	±0.003g
Stable Time	≤3s
Operation temp	5-25°C
Pan size	Φ90mm (Option)
Dimension	305*210*305mm
Draft shield size	175*165*200mm (Inner diameter)
LCD Size	94*24mm
Cal. weight	Internal calibration
G.W	6.0kg
N.W	4.5kg
Packing size	425*310*410mm
Interface	RS232 (Standard)
Sensor	Load cell
Alt Name	Precision Balance

ACCESSORIES FOR PURCHASE

No	Name	Description	Information
1	Weight set	Recommend corresponding accuracy calibration (1mg-20kg)	M1 level Suitable for 0.1g-0.01g



1



1



1



1



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com