



TURBIDITY METER BFU-5401

TURBIDITY METER BFU-5401

TURBIDITY METER



1. 7 inch high-resolution touch screen with friendly GUI.
2. The unique high-precision filter system makes the instrument more stable and accurate.
3. No blank calibration, automatic measurement, direct reading of concentration.
4. With built-in standard curves. Users can set up curves according to different measurement requirements.
5. Support zero point and up to 9-point calibration. Support calibration restoring function to restore factory calibration data.
6. With a large-capacity storage function, can store 5000 sets of test data.
7. Built-in thermal printers can print current data and stored data.

SPECIFICATIONS

| | |
|----------------------|--|
| Model | BFU-5401 |
| Measurement Method | 90° scattering method |
| Applications | Drinking water, surface water, sewage |
| Measuring Range | 0-500 NTU |
| Colorimetric Method | Tube Colorimetric |
| Accuracy | ≤5% |
| Resolution | 0.01 NTU |
| Light Source | Imported Silicon Photodiode |
| Stray Light | < 0.02 NTU |
| Display | 7-inch high-resolution 1024 * 600 touch screen |
| Output | USB (for data transfer) |
| Power | AC 220V/50Hz or AC 110V/60Hz |
| Ambient Temperature | (5-40) °C |
| Ambient Humidity | Relative humidity ≤ 85% (No condensation) |
| Dimensions/N.W. | 460x380x200 mm/8kg |
| Shipping size/G.W. | 520x450x300mm/10kg |
| Standard Accessories | Sample bottle x 2 pcs, Power cord, Manual |
| Alt Name | Turbidity Meter |



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com