



DOUBLE BEAM UV VISIBLE SPECTROPHOTOMETER BFU-604

DOUBLE BEAM UV VISIBLE SPECTROPHOTOMETER BFU-604

COLOR SCREEN SPECTROPHOTOMETER



1. 7 inches color screen and windows graphic interface.
2. Powerful functions like Photometric measurement, Quantitative measurement, Kinetics, Spectrum scan, DNA\Protein test, multiwavelength test, etc
3. In-house massive memory is capable of saving up to 1024M for test data & working curves.
4. Supports USB storage. The USB port can be used for data transfer, which is easily exported to Excel for further processing, analysis and storage.
5. Socket type deuterium and tungsten lamps can make lamps switching without optics debugging and are easy to be replaced.
6. Large sample chamber can accommodate 5-100mm cuvettes of all kinds.

SPECIFICATIONS

Model	BFU-604
Optical System	Double Beam, Grating 1200 lines/mm
Wavelength Range	190-1100 nm
Spectral Bandwidth	2nm
Wavelength Accuracy	±0.1nm @656.1nm
Wavelength Repeatability	≤0.1nm
Photometric Accuracy	0.2%T(0~100%T), ±0.002A(0-0.5A), ±0.004A(0.5-1A)
Photometric Repeatability	≤0.15%T (0-100%T), 0.001A(0-0.5A), 0.002A(0.5-1A)
Photometric Range	0-200%T, -0.3~3A, 0-9999C
Stray Light	≤0.03%T@220nm, 360nm
Stability	±0.0003A/h @500 nm
Baseline Flatness	±0.001A
Noise	0.0005A@500nm
Work Mode	T, A, C, E
Scanning Speed	Hi, Med, Low (Max. 3000nm/min)
Wavelength Setting	Auto
Display	7 inches Color Screen
Light Source	Deuterium & Tungsten lamp
Detector	Imported Silicon Photodiode
Cuvette Holder	10mm single hole cell holder
Output	USB drive, USB host, RS232
Power	AC 110-220V 50-60Hz
Shipping Size	880*690*520mm
Gross Weight	45kg
Standard Accessories	10mm glass cuvette x 4, 10mm quartz cuvette x 2, Power cord, User's Manual, PC software
Alt Name	Color Screen Spectrophotometer



FEATURES

1. 7 inches color screen and windows graphic interface.
2. Powerful functions like Photometric measurement, Quantitative measurement, Kinetics, Spectrum scan, DNA\Protein test, multiwavelength test, etc
3. In-house massive memory is capable of saving up to 1024M for test data & working curves.
4. Supports USB storage. The USB port can be used for data transfer, which is easily exported to Excel for further processing, analysis and storage.
5. Socket type deuterium and tungsten lamps can make lamps switching without optics debugging and are easy to be replaced.
6. Large sample chamber can accommodate 5-100mm cuvettes of all kinds.
7. Extensive accessories are optional, such as auto 8-cell holder, film holder, tube rack, peltier/sipper system, integrating sphere, reflection accessory, built-in printer, 21 CFR compliant software, etc.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com