



## MOISTURE ANALYZER BFU-6305

# MOISTURE ANALYZER BFU-6305

MOISTURE ANALYZER



1. LCD displays make operation easy and comfortable in the dark place.
2. One-button operation makes testing easier.
3. Provide 2 test modes of auto and timing
4. Supports PC connection. Wireless bluetooth printing is optional.
5. Can test the free water content of chemical raw materials, grain, mineral, biological product, food, pharmaceutical raw materials, paper, textile raw materials, etc.

## SPECIFICATIONS

Model	BFU-6305
Weighing Range	100g
Readability	1mg
Repeatability (3g samples)	0.002
Minimum Sample Amount	0.5g
Advised Sample Amount	3-5g
Heat up time	1-99 minutes, 1 minute interval
Temperature Program	Standard
Heating Temp Range	50-160°C
Display Content	Moisture%, Solid%, Weight, Time, Data etc
Heating Source	Halogen Lamp
Pan Size	100mm
Dimension/N.W.	220x350x140mm/5kg
Shipping size/G.W.	380x530x340mm/6kg
Standard Accessories	Calibration Weight, Power Cable, Manual
Alt Name	Moisture Analyzer



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)