





# CONDUCTIVITY METER BFU1BF1





### **CONDUCTIVITY METER BFU1BF1**

#### CONDUCTIVITY/DO METER



- Large LCD screen with controllable white backlight.
  Built-in microprocessor chip has Intelligent functions such as auto calibration, ATC, data storage, function settings,
- auto diagnosis, auto power off, and undervoltage prompt, etc.
- 3. Auto recognition of 8 conductivity standard solutions with 2 kinds of options: Europe & USA, and China.
- 4. It has functions of ATC, auto salinity compensation and manual pressure compensation.
- 5. Polarographic DO electrode, short polarization time (3-5 minutes).

### **SPECIFICATIONS**

Model	BFU1BF1
Cond. Measuring rang	Conductivity:
Cond. Resolution	0.01/0.1/1µS/cm; 0.01/0.1 mS/cm
Cond.Accuracy	±1.0% FS, Overall: ±1.5% FS
Temp. compensation	(0~100)°C(Auto/manual)
Electrode constant	0.1 / 1 / 10 cm-1
DO Measuring range	(0 ~ 20.00) mg/L(ppm), (0 ~ 200.0)%
DO Resolution	0.1/0.01 mg/L(ppm), 1/0.1 %
DO Accuracy	Electrode: ±0.10 mg/L, Instrument: ±0.40 mg/L
DO Response time	≤30s (25°C, 90%response)
DO Residual current	≤0.1 mg/L
DO Temp. compensation	(0 ~ 45)°C (auto)
DO Salinity compensation	(0 ~ 45) ppt (auto)
DO Pressure compensation	(66 ~ 200) kPa (manual)
DO Auto calibration	Air saturated by water, water saturated by air
DO Electrode type	Polarographic
Temp. Measuring range	(0 ~ 100)°C
Temp. Resolution	0.1°C
Temp. Accuracy	5 ~ 60°C: ±0.4°C Others: ±0.8°C
Other Data storage	200 sets
Other Power	AA batteries (1.5V x2)
Other Ambient Temp.	5 ~ 35 °C
Other Ambient humidity	<b>≤</b> 85%
Other IP grade	IP57 Dustproof and waterproof
Other Dimensions/N.W.	160x90x30mm/360g
Other Shipping size/G.W.	480x300x60mm/1KG
Standard Accessaries	Cond. electrode (K=1), DO electrode, Temperature probe, DO filling solution, Manual
Alt Name	Conductivity/DO Meter



## Biolab Scientific Ltd.