



SINGLE BEAM UV VISIBLE SPECTROPHOTOMETER BFU1C6

SINGLE BEAM UV VISIBLE SPECTROPHOTOMETER BFU1C6

FLASHING XENON LAMP SPECTROPHOTOMETER



1. 11-inch Touch Screen
2. High quality flashing xenon lamps are from Hamamatsu, which can start to test directly without preheating. The lamp can be used at least 5-year.
3. Powerful functions like Photometric measurement, Quantitative measurement, Kinetics, Spectrum scan, DNA\Protein test, Multiwavelength test, etc
4. Equipped with GLP/GMP functions, including user management, audit tracking, log inquiry, etc.
5. Support real-time sending of data via email and mobile SMS.
6. Adopts 3.0 Bluetooth protocol, with stable transmission and free interconnection within 10 meters.
7. Can be directly connected to laser printers via WiFi and thermal printers via

SPECIFICATIONS

Model	BFU1C6
Optical System	Single Beam, Grating 1200 lines/mm
Wavelength Range	190-1100 nm
Spectral Bandwidth	1nm
Wavelength Accuracy	±0.3nm
Wavelength Repeatability	±0.1nm
Photometric Accuracy	±0.2%T(0-100%T), ±0.0005A(0-0.5A), ±0.0008A(0.5-1A)
Photometric Repeatability	≤0.15%T (0-100%T), 0.0004A(0-0.5A), 0.0006A(0.5-1A)
Photometric Range	0-400%T, -4~4A
Resolution	0.00001Abs
Stray Light	≤0.03%T@220nm, 360nm
Stability	±0.0001A
Baseline Flatness	±0.0004A
Noise	0.0005A@500nm
Work Mode	T, A, C, E
Scanning Speed	Hi, Med, Low (Max. 6000nm/min)
Display	11-inch Touch Screen
Light Source	Xenon Lamp
Detector	Silicon Photodiode
Cuvette Holder	10mm manual 4-cell holder
Output	Cloud connectivity/Email/SMS/Bluetooth/WiFi
Power	AC 220V/50Hz or AC 110V/60Hz
Shipping Size	810*660*390mm
Gross Weight	27kg
Standard Accessories	10mm glass cuvette x 4, 10mm quartz cuvette x 2, Power cord, User's Manual
Alt Name	Flashing Xenon Lamp Spectrophotometer

FEATURES

1. 11-inch Touch Screen
2. High quality flashing xenon lamps are from Hamamatsu, which can start to test directly without preheating. The lamp can be used at least 5-year.
3. Powerful functions like Photometric measurement, Quantitative measurement, Kinetics, Spectrum scan, DNA\Protein test, Multiwavelength

test, etc

4. Equipped with GLP/GMP functions, including user management, audit tracking, log inquiry, etc.
5. Support real-time sending of data via email and mobile SMS.
6. Adopts 3.0 Bluetooth protocol, with stable transmission and free interconnection within 10 meters.
7. Can be directly connected to laser printers via WiFi and thermal printers via Bluetooth.
8. Extensive accessories are optional, such as auto 5-cell/8-cell holder, film holder, tube rack, integrating sphere, reflection accessory, peltier/sipper system, 21 CFR compliant software, etc.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com