



-25°C FREEZER BFUD-40-502

-25°C FREEZER BFUD-40-502

-25°C COMBINED REFRIGERATOR & FREEZER



Microprocessor control, ensure good inner temperature uniformity, accuracy is 0.1°C
Double outside doors and two independent chambers.
HC green refrigerant is energy-saving and environmentally friendly.
Wide available voltage range: 220V±10%.
Security
Safety door lock and controller password to prevent unauthorized access.
Built-in backup battery to display temperature and alarms when power failure or system error.
Visual and audible alarm system.
Power failure protection: turn-on delay of the cooling system after power failure.

SPECIFICATIONS

Model	BFUD-40-502
Temperature Range	F: -10 ~ -25°C; R: 2 ~ 8°C
Ambient Temperature	10~32°C
Capacity (L/Cu.Ft.)	R: 198 / 6.99; F: 102 / 3.6
Interior Dimensions (WxDxH) mm	R: 565x480x759; F: 461x465x600
Exterior Dimensions (WxDxH) mm	650x620x1980
Weight	100 kgs
Noise	49 dB
Controller	Microprocessor
Display	Digital
Sensor	NTC
Voltage and Frequency	220V±10%, 50/60Hz
Power	349 W
Electric Current	2.5 A
Power Consumption (kWh/24h)	3.3
High / Low Temp. Alarm	Yes
Power Failure Alarm	Yes, 8h
Sensor Error Alarm	Yes
Controller Error Alarm	Yes
Door Ajar Alarm	Yes
Refrigeration Type	R: Forced-air Cooling; F: Direct Cooling
Defrost	R: Auto; F: Manual
Compressor (Brand/pcs)	Chinese Brand / 2
Refrigerant / Weight	R290 / 74g
Door (pcs)	Foamed Solid Door / 2
Shelf (pcs)	4
Drawer (pcs)	4
Interior Cabinet Material	ABS
Exterior Cabinet Material	Coated Steel
Insulation Material	R: PURF (δ40mm); F: PURF (δ90mm)
Door Lock	Yes

LED Lamp	R: Yes; F: -
Test Hole (pcs)	2
Castors (pcs)	4
Leveling Feet (pcs)	2
Temperature Datalogger	Optional
Package	Carton box with pallet
Shipping Weight	120 kgs
Shipping Size (WxDxH)	725x700x2120
Shipping Volume	1.08 CBM
Alt Name	-25°C Combined Refrigerator & Freezer



FEATURES

Microprocessor control, ensure good inner temperature uniformity, accuracy is 0.1°C

Double outside doors and two independent chambers.

HC green refrigerant is energy-saving and environmentally friendly.

Wide available voltage range: 220V±10%.

Security

Safety door lock and controller password to prevent unauthorized access.

Built-in backup battery to display temperature and alarms when power failure or system error.

Visual and audible alarm system.

Power failure protection: turn-on delay of the cooling system after power failure.

Controller error protection: The cooling system will remember the normal working cycle and keep working depending on this memory when the controller or two sensors fail.

Humanized design

Adjustable shelves (Refrigerator) and drawers (Freezer) for easy storage.

Auto on/off LED light with manual switch on the control panel (Only for refrigerator).

Auto on/off cooling fan to prevent cold air from leaking out when the door is opening(Only for refrigerator).

Castors and adjustable feet for easy moving and fixation.

APPLICATIONS

Combined Refrigerator & Freezer are specially designed to store medicines, vaccines, blood plasma, reagents, and many other biological materials which are widely used in research institutions, clinics, and electronic and medical fields.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com