PRODUCT CATALOG

CLASS B AUTOCLAVE BGA-1102

CE ISO9001 CERTIFIED

www.biolabscientific.com

CLASS B AUTOCLAVE BGA-1102

CLASS B AUTOCLAVE

Based on the new class B, have 3 pulsating vacuum, Vacuum up to -0.9Bar(-0.09Mpa). Residual humidity is <0.2.Suitable to sterilizing wrap, unwrap,solid, porous, hollow device.
Use imported&advanced 16-bit microprocessors,easy to operate. Most suitable for the Dept of Stomatology,Ophthalmology, Surgery and Lab.
With B&D test and vacuum test procedures. To test the penetrability.
Chamber punched by Stainless Steel (#304, thickness: 2.5mm), together with the jet type of steam generator ensure the efficient sterilizing.
With an alarm system for the waste water tank, avoid the waste water from entering into the sterilizing circulation, make the sterilizing completely.
Precise LCD display and advanced self-test system ensure you get the working data freely.

SPECIFICATIONS

Model	BGA-1102
Capacity	18L
Sterilization Temperature	134°C/121°C
Working Pressure	
Features	
Power	1800W
Voltage	AC220V/110V±10%
Frequency	50/60Hz±lHz
Tank Capacity	18Litres
Appearance size	445X550X395mm
Inside Dimension	Ø249x355mm
Outside Dimension	670x550x500mm
Sterilization level	European Class B standard
Sterilizing temp.	134°C/121°C
Special sterilization	Kill active HV,HBV,BSE and spore
Dry procedure	Strong vacuum drying,the residual humidity<0.2%
Display	Widescreen LCD
Test	Bowie&Dick Steam penetration test, vacuum test , Helix test
Safety	Safety valve, Double Pressure lock Automatic check.
Sterilizing record	Optional USB and printer (internal or external) to record the sterilization process
Water supply system	3L distiller water tank,3L waste water tank
Clean procedure	Automatic clean inside pipe and steam generator
Instrument containers	5 levels with 3 Round trays
G"W	48kg
Alt Name	Class B Autoclave

FEATURES

Based on the new class B, have 3 pulsating vacuum, Vacuum up to -0.9Bar(-0.09Mpa). Residual humidity is <0.2.Suitable to sterilizing wrap, unwrap,solid, porous, hollow device.
Use imported&advanced 16-bit microprocessors,easy to operate. Most suitable for the Dept of Stomatology,Ophthalmology, Surgery and Lab.
With B&D test and vacuum test procedures. To test the penetrability.
Chamber punched by Stainless Steel (#304, thickness: 2.5mm), together with the jet type of steam generator ensure the efficient sterilizing.

With an alarm system for the waste water tank, avoid the waste water from entering into the sterilizing circulation, make the sterilizing completely.
Precise LCD display and advanced self-test system ensure you get the working data freely.
Double lock door system for safety during operating.
Optional inbuilt mini-printer or USB connector to record the process of sterilizing.

Biolab Scientific Ltd.
Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com