



## DENTAL AUTOCLAVE BGA1E1 (BADT-701)

# DENTAL AUTOCLAVE BGA1E1

## AUTOCLAVE (STEAM STERILIZER) CLASS B

Unique traceability system identifies load in different clinical and medical grade applications. Effectively sterilizes miscellaneous solid, hollow or porous (wrapped/unwrapped) materials and meets the requirement of today's demanding clinical environment. Automatic sterilization along with safety operating features and drying function makes it a perfect solution for effective and rapid steam sterilization. Innovated to comply with international standards, reliable solution for sterilization needs of reusable equipment.



- Fast and simple operation, Open water tank
- Open storage tank, waste water tank, easy to clean
- Concealment type interface
- Drain valve, output interface conceal
- Each interface front cover is open, easy to operate
- Chamber material is Stainless Steel (#304)
- Test the pot body tightness
- Built-in printer: The disinfection process date and data automatically printed
- USB: Built-in USB interface, End of the work, the information stored in the U disk automatically
- Automatic identification of fault protection system, Safe and fast judgment fault

## SPECIFICATIONS

Model	BGA1E1
Old Model	BADT-701
Capacity	18 L
Sterilization Temperature	121°C, 134°C
Vacuum degree	-0.09Mpa
Steam leakage test	Yes
Residual humidity	<0.2%
121°C Solid	Yes
121°C Porous	Yes
121°C Hollow	Yes
134°C Porous	Yes
134°C Hollow	Yes
B&D Test	Yes
Vacuum Test	Yes
Penetration test	Yes
Chamber Dimension	Ø249x355 mm
Overall Dimension (LxWxH)	471x505x540 mm
Display	7" full-color touch LCD screen
Door	Automatic locking mechanism
Weight	60 kg
Power	1800 W
Power Supply	AC220V/110V±10%
50/60Hz±1Hz	Printer
Alt Name	Autoclave (Steam Sterilizer) Class B

## FEATURES

Fast and simple operation, Open water tank  
Open storage tank, waste water tank, easy to clean  
Concealment type interface  
Drain valve, output interface conceal  
Each interface front cover is open, easy to operate  
Chamber material is Stainless Steel (#304)  
Test the pot body tightness  
Built-in printer: The disinfection process date and data automatically printed  
USB: Built-in USB interface, End of the work, the information stored in the U disk automatically  
Automatic identification of fault protection system, Safe and fast judgment fault  
Semi-automatic fault identifying system  
3 pulsating vacuum  
Suitable for sterilizing wrap, unwrap, solid, porous, hollow device  
Use imported & advanced 16-bit microprocessor, easy to operate  
The jet type of steam generator, ensure the efficient sterilization  
With alarm system for waste water tank, avoid the waste water to enter into the sterilizing circulation  
Advanced self-test system ensure you get the working data freely  
The steam generator cleaning procedures, Clean the machine lines automatically every 30 times to avoid jams  
Open water tank, Avoid growing chloride toxins  
Alarm: Storage tank water shortage, waste water tank filled with water  
Powerful cooling system, Effective condensing steam automatic electronic security door lock.

## APPLICATIONS

Medical, Dental, Laboratory, Pharmaceutical, Research.



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada  
Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)