BioLAB

PRODUCT CATALOG



TEMPERATURE AND HUMIDITY CHAMBER
BGE-1003

CE ISO9001 CERTIFIED

www.biolabscientific.com

TEMPERATURE AND HUMIDITY CHAMBER BGE-1003

CONSTANT TEMPERATURE AND HUMIDITY INCUBATOR




·The shell is made of cold-rolling steel with static spray plastics, the working chamber is made of mirror
stainless steel, the shelves can be adjusted optionally;
·PAMMA II control system, LCD screen displays temperature and time, over -temperature alarm function;
·Use centrifugal fan to make the temperature of the working room uniform and stable
·Double door design, observation glass inner door ;
·Test holes are equipped on both sides, internal diameter is 30mm;
·Well-known international brand c compressor, non-CF C refrigerant
·Equipped with mechanical lock ,
·Integrated type refrigeration sys tem,

SPECIFICATIONS

Model	BGE-1003
Chamber Capacity	400L
Temperature Range	0-60°C Without Humidifying
Temperature Range With Humidifying (°C)	10-60°C
Type	Constant Temperature & Humidity / Mould Incubator
Temperature Resolution (°C)	0.1
Temperature Fluctuation at 25°C (°C)	±0.5
Temperature Uniformity at 25°C (°C)	±1
Humidity Range (%)	50-90
Humidity Fluctuation (%)	±5
Power (W)	1700
Timer Range (min/h)	0-9999
Internal Dimensions (W*D*H)	600x640x1050mm
External Dimensions (W*D*H)	745x930x1695mm
Number of Shelves (pcs)	4
Net/Gross Weight (kg)	162/202
Package Size (mm)	890x1120x1880
Alt Name	Constant Temperature and Humidity Incubator









FEATURES

·The shell is made of cold-rolling steel with static spray plastics, the working chamber is made of mirror
stainless steel, the shelves can be adjusted optionally;
·PAMMA II control system, LCD screen displays temperature and time, over -temperature alarm function;
·Use centrifugal fan to make the temperature of the working room uniform and stable

·Double door design, observation glass inner door ;
·Test holes are equipped on both sides, internal diameter is 30mm;
·Well-known international brand c compressor, non-CF C refrigerant
·Equipped with mechanical lock ,
·Integrated type refrigeration sys tem,
·Imported humidity sensor , electric heating humidification sys tem, large capacity w ater t ank;
·Programmable design, it c an be se t 30 segments 99 cycles;
·Power supply r ecover y func tion, da ta will no t be los t when power failure and the system halted.

Biolab Scientific Ltd.
Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com