BioLAB

PRODUCT CATALOG



BIOCHEMICAL INCUBATOR BGE-102

CE ISO9001 CERTIFIED

www.biolabscientific.com

COOLING INCUBATOR BGE-102

BIOCHEMICAL INCUBATOR



The shell is made of cold-rolling steel with static spray plastics, the working chamber is made of mirror or stainless steel, the shelves can be adjusted optionally;
PAMMA I control system;
With timing functions;
Lighting device in working chamber (mould incubator is equipped with UV light);
Large vie wing angle he at preservation vacuum toughened glass;
Power supply recovery function, data will not be lost when power failure and system halted.

SPECIFICATIONS

Model	BGE-102
Capacity	150L
Temperature Range	0-50℃
Temperature Accuracy	
Temperature Resolution	0.1℃
Temperature Fluctuation	±1℃ Heating, ±2℃ Cooling
Temperature Uniformity at 37℃	±2℃
Type	Biochemical Incubator
Internal Dimensions (W*D*H)	500*335*955mm
External Dimensions (W*D*H)	595*580*1232mm
Power	300 W
Timer Range	0-999 h
Shelves (Standard/Max.)	3/5
Load per Shelf	15 kg
Net/Gross Weight	79/111 kg
Package Size	730*680*1400mm
Alt Name	Biochemical Incubator

APPLICATIONS

The product is applicable in scientific research institutions, universities and colleges, manufacturing enterprises for environmental protection, sanitation and epidemic prevention, drug testing, farm livestock and aquatic products. It is a dedicated thermostatic equipment for water analysis, cultivation and conservation of bacteria, mould and microorganism by BOD measurement, planting and breeding experiments.

Biolab Scientific Ltd.
Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com