BioLAB

PRODUCT CATALOG



BIOCHEMICAL INCUBATOR BGE-202

CE ISO9001 CERTIFIED

www.biolabscientific.com

COOLING INCUBATOR BGE-202

BIOCHEMICAL INCUBATOR



The shell is made of cold-rolling steel with static spray plastics, the working chamber is
made of mirror or stainless steel, the shelves can be adjusted optionally;
PMMA II operating system, with over temperature alarm and self -diagnosis function;
The fan has 6-stage speed regulation, which can meet the different requirements
8W fluorescent lamp in working chamber (mould incubator is equipped with 8W UV light);
Large viewing angle heat preservation vacuum toughened glass is convenient f or users t o observe;
Equipped with 220V power socket;
Frequency conversion refrigeration system, environmental protection refrigerant

SPECIFICATIONS

Model	BGE-202
Capacity	150 L
Temperature Range	0-60°C
Temperature Accuracy	
Temperature Resolution	0.1°C
Temperature Fluctuation	±0.7°C Heating, ±1°C Cooling
Temperature Uniformity at 37°C	±1.5°C
Type	Biochemical Incubator
Internal Dimensions (W*D*H)	500*370*815mm
External Dimensions (W*D*H)	595*580*1232mm
Power	500 W
Timer Range	0-9999 min/h
Shelves (Standard/Max.)	3/5
Load per Shelf	15 kg
Net/Gross Weight	82/114 kg
Package Size	700x660x1490mm
Alt Name	Biochemical Incubator

FEATURES

The shell is made of cold-rolling steel with static spray plastics, the working chamber is
made of mirror or stainless steel, the shelves can be adjusted optionally;
PMMA II operating system, with over temperature alarm and self -diagnosis function;
The fan has 6-stage speed regulation, which can meet the different requirements
8W fluorescent lamp in working chamber (mould incubator is equipped with 8W UV light);
Large viewing angle heat preservation vacuum toughened glass is convenient f or users t o observe;
Equipped with 220V power socket;
Frequency conversion refrigeration system, environmental protection refrigerant (R134a),
high efficiency, low energy consumption, full temperature continuous frost-free operation;
Adopt imported compressor unit , low noise, stable performance;
Power supply recovery function, data will not be lost when power failure and system halt.



Biolab Scientific Ltd.
Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com